

TXD2-24V-3 Information

Heisener.com

Part Number TXD2-24V-3

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 2A 24V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TXD2-24V-3 Specifications

Manufacturer Part NumberTXD2-24V-3ManufacturerPanasonic Electric WorksCategoryRelaysPackage-SeriesTX-DRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough Hole		
CategoryRelaysPackage-SeriesTX-DRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeaturesSealed - Fully	Manufacturer Part Number	TXD2-24V-3
Package - Series TX-D Relay Type General Purpose Coil Type Non Latching Coil Current 12.9mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 220VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully	Manufacturer	Panasonic Electric Works
Package - Series TX-D Relay Type General Purpose Coil Type Non Latching Coil Current 12.9mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 220VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully	Category	Relays
SeriesTX-DRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeaturesSealed - Fully		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current12.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeaturesSealed - Fully	Package	-
Coil TypeNon LatchingCoil Current12.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeaturesSealed - Fully	Series	TX-D
Coil Current 12.9mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 220VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully	Relay Type	General Purpose
Coil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time4msRelease Time4msFeaturesSealed - Fully	Coil Type	Non Latching
Contact Form C DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 220VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully	Coil Current	12.9mA
Contact Rating (Current) Switching Voltage 220VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully	Coil Voltage	24VDC
Switching Voltage 220VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features Sealed - Fully	Switching Voltage	220VDC - Max
Operate Time4msRelease Time4msFeaturesSealed - Fully	Turn On Voltage (Max)	18 VDC
Release Time 4ms Features Sealed - Fully	Turn Off Voltage (Min)	2.4 VDC
Features Sealed - Fully	Operate Time	4ms
	Release Time	4ms
Mounting Type Through Hole	Features	Sealed - Fully
	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

TXD2-24V-3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TXD2-24V-3 Payment Methods



















TXD2-24V-3 Shipping Methods













If you have any question about TXD2-24V-3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com