

TXD2-5V-6 Information

www.heisener.com

For Reference Only

Part Number TXD2-5V-6

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GENERAL PURPOSE DPDT 2A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TXD2-5V-6 Specifications

Manufacturer Part Number TXD2-5V-6 Manufacturer Panasonic Electric Works Category Relays Signal Relays, Up to 2 Amps Package - Series TX-D Relay Type General Purpose Coil Type Non Latching Coil Current 56.2mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesTX-DRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current56.2mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	TXD2-5V-6
Package-SeriesTX-DRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current56.2mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package - TX-D Relay Type General Purpose Coil Type Non Latching Coil Current 56.2mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style Poon Contact RX-D Contact	Category	Relays
SeriesTX-DRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current56.2mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current56.2mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current56.2mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time4msRelease Time4msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	TX-D
Coil Current 56.2mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Current	56.2mA
Contact Rating (Current) Switching Voltage 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	5VDC
Switching Voltage 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Ams Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style 3.75 VDC 4ms Sexual Sex	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style O.5 VDC 4ms Features PC Pin	Switching Voltage	220VDC - Max
Operate Time 4ms Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	3.75 VDC
Release Time 4ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.5 VDC
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	4ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	4ms
Termination Style PC Pin	Features	Sealed - Fully
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

TXD2-5V-6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TXD2-5V-6 Payment Methods





















TXD2-5V-6 Shipping Methods













If you have any question about TXD2-5V-6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com