

TXS2-4.5V Information

www.helsener.com

For Reference Only

Part Number TXS2-4.5V

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 1A 4.5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TXS2-4.5V Specifications

| Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Signal Relays, Up to 2 Amps Package - Series TX-S Relay Type General Purpose Coil Type Non Latching Coil Current 11.1mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time Features Sealed - Fully Mounting Type Through Hole PC Pin Report errors? | | |
|--|--------------------------|-----------------------------|
| CategoryRelaysPackage-SeriesTX-SRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11.1mACoil Voltage4.5 VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage110 VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)0.45 VDCOperate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin | Manufacturer Part Number | |
| Package-SeriesTX-SRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11.1mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage110VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)0.45 VDCOperate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin | Manufacturer | Panasonic Electric Works |
| Package - TX-S Relay Type General Purpose Coil Type Non Latching Coil Current 11.1mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style | Category | Relays |
| SeriesTX-SRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11.1mACoil Voltage4.5 VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage110 VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)0.45 VDCOperate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin | | Signal Relays, Up to 2 Amps |
| Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11.1mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage110VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)0.45 VDCOperate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin | Package | - |
| Coil TypeNon LatchingCoil Current11.1mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage110VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)0.45 VDCOperate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin | Series | TX-S |
| Coil Current11.1mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage110VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)0.45 VDCOperate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin | Relay Type | General Purpose |
| Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Coil Type | Non Latching |
| Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 110VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time Sms Release Time Features Sealed - Fully Mounting Type Through Hole Termination Style | Coil Current | 11.1mA |
| Contact Rating (Current) Switching Voltage 110VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style | Coil Voltage | 4.5VDC |
| Switching Voltage 110VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Contact Form | DPDT (2 Form C) |
| Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time Sms Features Sealed - Fully Mounting Type Through Hole Termination Style 3.6 VDC 0.45 VDC 5ms Femany 5ms Fend Femany Fema | Contact Rating (Current) | 1A |
| Turn Off Voltage (Min) Operate Time Sms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style O.45 VDC Sms Freatures PC Pin | Switching Voltage | 110VDC - Max |
| Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Turn On Voltage (Max) | 3.6 VDC |
| Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Turn Off Voltage (Min) | 0.45 VDC |
| Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin | Operate Time | 5ms |
| Mounting Type Through Hole Termination Style PC Pin | Release Time | 5ms |
| Termination Style PC Pin | Features | Sealed - Fully |
| | Mounting Type | Through Hole |
| Report errors? | Termination Style | PC Pin |
| | | Report errors? |

TXS2-4.5V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TXS2-4.5V Payment Methods



















TXS2-4.5V Shipping Methods













If you have any question about TXS2-4.5V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com