

### **TXS2-6V Information**



For Reference Only

Part Number TXS2-6V

Manufacturer Panasonic Electric Works

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GENERAL PURPOSE DPDT 1A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **TXS2-6V Specifications**

Manufacturer Part NumberTXS2-6VManufacturerPanasonic Electric WorksCategoryRelaysSignal Relays, Up to 2 AmpsPackage-SeriesTX-SRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage110VDC - MaxTurn On Voltage (Max)4.8 VDCTurn Off Voltage (Min)0.6 VDCOperate Time5ms		
Category  Relays Signal Relays, Up to 2 Amps  Package - Series TX-S Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 5ms	Manufacturer Part Number	TXS2-6V
Signal Relays, Up to 2 Amps  Package - Series TX-S  Relay Type General Purpose  Coil Type Non Latching  Coil Current 8.3mA  Coil Voltage 6VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 1A  Switching Voltage 110VDC - Max  Turn On Voltage (Max) 4.8 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 5ms	Manufacturer	Panasonic Electric Works
Package - Series TX-S Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 5ms	Category	Relays
Series TX-S Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 5ms		Signal Relays, Up to 2 Amps
Relay Type Coil Type Non Latching Coil Current 8.3mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 5ms	Package	-
Coil Type Non Latching Coil Current 8.3mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 4.8 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 5ms	Series	TX-S
Coil Current 8.3mA  Coil Voltage 6VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 1A  Switching Voltage 110VDC - Max  Turn On Voltage (Max) 4.8 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 5ms	Relay Type	General Purpose
Coil Voltage 6VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 1A  Switching Voltage 110VDC - Max  Turn On Voltage (Max) 4.8 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 5ms	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  110VDC - Max  Turn On Voltage (Max)  4.8 VDC  Turn Off Voltage (Min)  Operate Time  5ms	Coil Current	8.3mA
Contact Rating (Current)  Switching Voltage  110VDC - Max  Turn On Voltage (Max)  4.8 VDC  Turn Off Voltage (Min)  0.6 VDC  Operate Time  5ms	Coil Voltage	6VDC
Switching Voltage 110VDC - Max  Turn On Voltage (Max) 4.8 VDC  Turn Off Voltage (Min) 0.6 VDC  Operate Time 5ms	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  4.8 VDC  Turn Off Voltage (Min)  Operate Time  5ms	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time  0.6 VDC 5ms	Switching Voltage	110VDC - Max
Operate Time 5ms	Turn On Voltage (Max)	4.8 VDC
	Turn Off Voltage (Min)	0.6 VDC
	Operate Time	5ms
Release Time 5ms	Release Time	5ms
Features Sealed - Fully	Features	Sealed - Fully
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

### **TXS2-6V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **TXS2-6V Payment Methods**



















## **TXS2-6V Shipping Methods**













If you have any question about TXS2-6V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com