

TXS2-L-1.5V Information



For Reference Only

Part Number TXS2-L-1.5V

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 1A 1.5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TXS2-L-1.5V Specifications

Manufacturer Part Number Manufacturer Panasonic Electric Works Relays Signal Relays, Up to 2 Amps Package Series TX-S Relay Type General Purpose Latching, Single Coil Coil Current 23.3mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 1.2 VDC Turn Off Voltage (Min) Operate Time Sms Release Time Features Sealed - Fully Mounting Type Through Hole PC Pin Report errors?		
Category Relays Signal Relays, Up to 2 Amps - Series TX-S Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 23.3mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 1.2 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Manufacturer Part Number	TXS2-L-1.5V
Signal Relays, Up to 2 Amps Package - Series TX-S Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 23.3mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 1.2 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Manufacturer	Panasonic Electric Works
Package - Series TX-S Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 23.3mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 1.2 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Category	Relays
Series TX-S Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 23.3mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 110VDC - Max Turn On Voltage (Max) 1.2 VDC Turn Off Voltage (Min) Operate Time 5ms Release Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style		Signal Relays, Up to 2 Amps
Relay Type Coil Type Latching, Single Coil Coil Current 23.3mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) LA Switching Voltage 110VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time Sms Release Time Sealed - Fully Mounting Type Through Hole Termination Style General Purpose Latching, Single Coil Latching, Si	Package	-
Coil Type Latching, Single Coil Coil Current 23.3mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 1.2 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Series	TX-S
Coil Current 23.3mA Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 1.2 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 1.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 1.2 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Single Coil
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 110VDC - Max Turn On Voltage (Max) 1.2 VDC Turn Off Voltage (Min) Operate Time 5ms Release Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Current	23.3mA
Contact Rating (Current) Switching Voltage 110VDC - Max Turn On Voltage (Max) 1.2 VDC Turn Off Voltage (Min) Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	1.5VDC
Switching Voltage Turn On Voltage (Max) 1.2 VDC Turn Off Voltage (Min) Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style 1.2 VDC Through Hole PC Pin	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	110VDC - Max
Operate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	1.2 VDC
Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

TXS2-L-1.5V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TXS2-L-1.5V Payment Methods



















TXS2-L-1.5V Shipping Methods













If you have any question about TXS2-L-1.5V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com