

TXS2SA-24V Information



For Reference Only

Part Number TXS2SA-24V

Manufacturer Panasonic Electric Works

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 1A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









TXS2SA-24V Specifications

Manufacturer Part NumberTXS2SA-24VManufacturerPanasonic Electric WorksCategoryRelaysPackage-SeriesTX-SRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current2.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage110VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time5msRelease Time5msFeaturesSealed - Fully	-	
Category Relays Signal Relays, Up to 2 Amps Package - Series TX-S Relay Type General Purpose Coil Type Non Latching Coil Current 2.9mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Sms Release Time Signal Relays Signal Relays, Up to 2 Amps Fur Signal Relays, Up to 2 Amps 11X-S Signal Relays, Up to 2 Amps Fur Signal Relays, Up to 2 Amps Fur Signal Relays, Up to 2 Amps 11X-S Sens Signal Relays, Up to 2 Amps Fur Signal Relays Fur Signal Rel	Manufacturer Part Number	TXS2SA-24V
Package - Series TX-S Relay Type General Purpose Coil Type Non Latching Coil Current 2.9mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 5ms Release Time 5ms	Manufacturer	Panasonic Electric Works
Package - Series TX-S Relay Type General Purpose Coil Type Non Latching Coil Current 2.9mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 5ms Release Time 5ms	Category	Relays
Series TX-S Relay Type General Purpose Coil Type Non Latching Coil Current 2.9mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 5ms Release Time 5ms		Signal Relays, Up to 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 2.9mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 5ms Release Time 5ms	Package	-
Coil TypeNon LatchingCoil Current2.9mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage110VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time5msRelease Time5ms	Series	TX-S
Coil Current 2.9mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 5ms Release Time 5ms	Relay Type	General Purpose
Coil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage110VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time5msRelease Time5ms	Coil Type	Non Latching
Contact Form C) Contact Rating (Current) Switching Voltage 110VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 5ms Release Time 5ms	Coil Current	2.9mA
Contact Rating (Current) Switching Voltage 110VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 5ms Release Time 5ms	Coil Voltage	24VDC
Switching Voltage 110VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 5ms Release Time 5ms	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 5ms Release Time 5ms	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time Sms Release Time 5ms	Switching Voltage	110VDC - Max
Operate Time5msRelease Time5ms	Turn On Voltage (Max)	19.2 VDC
Release Time 5ms	Turn Off Voltage (Min)	2.4 VDC
	Operate Time	5ms
Features Sealed - Fully	Release Time	5ms
	Features	Sealed - Fully
Mounting Type Surface Mount	Mounting Type	Surface Mount
Termination Style Gull Wing	Termination Style	Gull Wing
Report errors?		Report errors?

TXS2SA-24V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

TXS2SA-24V Payment Methods



















TXS2SA-24V Shipping Methods













If you have any question about TXS2SA-24V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com