

### **TXS2SS-9V Information**



For Reference Only

Part Number TXS2SS-9V

Manufacturer Panasonic Electric Works

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GENERAL PURPOSE DPDT 1A 9V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **TXS2SS-9V Specifications**

Manufacturer Part NumberTXS2SS-9VManufacturerPanasonic Electric WorksCategoryRelaysBackage-SeriesTX-SRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current5.6mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage110VDC - MaxTurn On Voltage (Max)7.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeSurface Mount		
Category  Relays  Signal Relays, Up to 2 Amps	Manufacturer Part Number	TXS2SS-9V
Package - Series TX-S Relay Type General Purpose Coil Type Non Latching Coil Current 5.6mA Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 7.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 5ms Release Time 5ms Features Sealed - Fully	Manufacturer	Panasonic Electric Works
Package - Series TX-S Relay Type General Purpose Coil Type Non Latching Coil Current 5.6mA Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 110VDC - Max Turn On Voltage (Max) 7.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 5ms Release Time 5ms Features Sealed - Fully	Category	Relays
Series         TX-S           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         5.6mA           Coil Voltage         9VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         1A           Switching Voltage         110VDC - Max           Turn On Voltage (Max)         7.2 VDC           Turn Off Voltage (Min)         0.9 VDC           Operate Time         5ms           Release Time         5ms           Features         Sealed - Fully		Signal Relays, Up to 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 5.6mA  Coil Voltage 9VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 1A  Switching Voltage 110VDC - Max  Turn On Voltage (Max) 7.2 VDC  Turn Off Voltage (Min) 0.9 VDC  Operate Time 5ms  Release Time 5ms  Features Sealed - Fully	Package	-
Coil TypeNon LatchingCoil Current5.6mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage110VDC - MaxTurn On Voltage (Max)7.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time5msRelease Time5msFeaturesSealed - Fully	Series	TX-S
Coil Current  Coil Voltage  9VDC  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  1A  Switching Voltage  110VDC - Max  Turn On Voltage (Max)  7.2 VDC  Turn Off Voltage (Min)  0.9 VDC  Operate Time  5ms  Release Time  5ms  Features  Sealed - Fully	Relay Type	General Purpose
Coil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage110VDC - MaxTurn On Voltage (Max)7.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time5msRelease Time5msFeaturesSealed - Fully	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  110VDC - Max  Turn On Voltage (Max)  7.2 VDC  Turn Off Voltage (Min)  0.9 VDC  Operate Time  5ms  Release Time  5ms  Features  Sealed - Fully	Coil Current	5.6mA
Contact Rating (Current)  Switching Voltage  110VDC - Max  Turn On Voltage (Max)  7.2 VDC  Turn Off Voltage (Min)  0.9 VDC  Operate Time  5ms  Release Time  5ms  Features  Sealed - Fully	Coil Voltage	9VDC
Switching Voltage 110VDC - Max  Turn On Voltage (Max) 7.2 VDC  Turn Off Voltage (Min) 0.9 VDC  Operate Time 5ms  Release Time 5ms  Features Sealed - Fully	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Sms  Release Time  5ms  Features  Sealed - Fully	Contact Rating (Current)	1A
Turn Off Voltage (Min)  Operate Time  Sms  Release Time  5ms  Features  Sealed - Fully	Switching Voltage	110VDC - Max
Operate Time5msRelease Time5msFeaturesSealed - Fully	Turn On Voltage (Max)	7.2 VDC
Release Time5msFeaturesSealed - Fully	Turn Off Voltage (Min)	0.9 VDC
Features Sealed - Fully	Operate Time	5ms
	Release Time	5ms
Mounting Type Surface Mount	Features	Sealed - Fully
* · ·	Mounting Type	Surface Mount
Termination Style Gull Wing	Termination Style	Gull Wing
Report errors?		Report errors?

#### **TXS2SS-9V Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **TXS2SS-9V Payment Methods**



















### **TXS2SS-9V Shipping Methods**













If you have any question about TXS2SS-9V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com