

U213J61ZQE22

U213J61ZQE22 Information

Heisener.com	Part Number Manufacturer Category Description Package	U213J61ZQE22 C&K Switches Rocker Switches SWITCH ROCKER SP3T 5A 120V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



U213J61ZQE22 Specifications

Manufacturer Part Number U213/61ZQE22 Manufacturer C&K Category Switches Package - Series 7000 Circuit SP3T Switch Function On-On-Mom Current Rating SA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Padelle Color - Actuator/Cap Black Actuator Marking No Marking Illumination Type, Color - Mounting Type Solder Lug Ingress Protection Solder Lug Ingress Protection - Features Jumper needed to achieve triple throw		
Category Switches Rocker Switches Package - Series 7000 Circuit SP3T Switch Function On-On-Mom Current Rating SA (AC/DC) Voltage Rating - AC Savich Yoltage Rating - DC Savich Actuator Type Padele Color - Actuator/Cap Black Rotuing Type, Color - Illumination Voltage (Nominal) - Mounting Type Solder Lug Termination Style Solder Lug Ingress Protection - Features Junper needed to achieve triple throw Paceduct Dimensions Rectangular - 15.24mm x 12.70mm	Manufacturer Part Number	U213J61ZQE22
ConstructionRocker SwitchesPackage-Series7000CircuitSP3TSwitch FunctionOn-On-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypePaddleColor - Actuator/CapBlackActuator MarkingNo MarkingIllumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FaturesJumpr needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Manufacturer	C&K
Package-Series7000CircuitSP3TSwitch FunctionOn-On-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VColor - Actuator/CapBlackColor - Actuator/Cap-Ilumination Type, Color-Ilumination Type9ael Mount, Snap-InMounting TypeSolder LugIngress Protection-FaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular 1.5.24mm x1.2.70mm	Category	Switches
Series7000CircuitSP3TSwitch FunctionOn-On-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypePadleColor - Actuator/CapBlackActuator Marking-Ilumination Type, Color-Ilumination Voltage (Nominal)-Mouting TypeSolder LugIngers ProtectionSolder LugIngers Protection-FeaturesJumpr needed to achieve triple throwPanel Cutout DimensionsKetangular - 15.24mm x 12.70mm		Rocker Switches
CircuitSP3TSwitch FunctionOn-On-MornCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCS8VActuator TypePaddleActuator TypeBlackColor - Actuator/CapSN ArkingIlumination Type, Color-Ilumination Voltage (Nominal)-Mouting TypeSolder LugTermination StyleSolder LugIngress ProtectionJumer needed to achieve triple throwFeaturesJumer needed to achieve triple throwPanel Cutout DimensionsSectangular 15.24mm x 12.70mm	Package	-
Switch FunctionOn-On-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSa VaActuator TypePaddleColor - Actuator/CapBlackRutuntor Marking-Ilumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypeSolder LugIngress ProtectionSolder LugFacturesJumper needed to achieve triple throwRated to Actuator Dimensions-	Series	7000
Current RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypePaddleColor - Actuator/CapBlackActuator MarkingNo MarkingIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypeSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular. 12.70mm	Circuit	SP3T
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypePaddleColor - Actuator/CapBlackActuator MarkingNo MarkingIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination Style-Ingress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Switch Function	On-On-Mom
Voltage Rating - DC28VActuator TypePaddleColor - Actuator/CapBlackActuator MarkingNo MarkingIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular. 15.24mm x 12.70mm	Current Rating	5A (AC/DC)
Actuator TypePaddleColor - Actuator/CapBlackActuator MarkingNo MarkingIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular 15.24mm x 12.70mm	Voltage Rating - AC	120V
Color - Actuator/CapBlackActuator MarkingNo MarkingIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Voltage Rating - DC	28V
Actuator MarkingNo MarkingIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular 15.24mm x 12.70mm	Actuator Type	Paddle
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Color - Actuator/Cap	Black
Illumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Actuator Marking	No Marking
Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Illumination Type, Color	-
Termination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Illumination Voltage (Nominal)	-
Ingress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Mounting Type	Panel Mount, Snap-In
FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Termination Style	Solder Lug
Panel Cutout Dimensions Rectangular - 15.24mm x 12.70mm	Ingress Protection	-
	Features	Jumper needed to achieve triple throw
Report errors?	Panel Cutout Dimensions	Rectangular - 15.24mm x 12.70mm
		Report errors?

U213J61ZQE22 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

U213J61ZQE22 Payment Methods



U213J61ZQE22 Shipping Methods



If you have any question about U213J61ZQE22, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com