

# U215J52ZQE22

### U215J52ZQE22 Information

Heisener.com	Part Number Manufacturer Category Description Package	U215J52ZQE22 C&K Switches Rocker Switches SWITCH ROCKER SP3T 5A 120V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# U215J52ZQE22 Specifications

Manufacturer Part Number U215J52ZQE22   Manufacturer C&K   Category Switches   Package -   Series 7000   Circuit SP3T   Switch Function Mom-On-Mom   Current Rating SA (AC/DC)   Voltage Rating - AC 28V   Voltage Rating - DC 28V   Actuator Type Concave (Standard V) - Illuminated   Cloror - Actuator/Cap Black   Allumination Type, Color -   Illumination Type Solder Lug   Mounting Type Solder Lug   Ingress Protection Solder Lug   Ingress Protection Solder Lug   Ingress Protection -   Panel Cutout Dimensions Rectangular - 15.24mm x 12.70mm		
Category Switches   Rocker Switches   Package -   Series 7000   Circuit SP3T   Switch Function Mon-On-Mom   Current Rating SA (AC/DC)   Voltage Rating - AC 28V   Yoltage Rating - DC 28V   Actuator Type Concave (Standard V) - Illuminated   Color - Actuator/Cap Black   Illumination Type, Color -   Illumination Voltage (Nominal) -   Mounting Type Panel Mount, Snap-In   Ingress Protection -   Features Junper needed to achieve triple throw   Pacedato to achieve triple throw -	Manufacturer Part Number	U215J52ZQE22
ConstructionRocker SwitchesPackage-Series7000CircuitSP3TSwitch FunctionMom-On-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeConcave (Standard V) - IlluminatedColor - Actuator/CapBlackActuator MarkingNo MarkingIllumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Manufacturer	C&K
Package-Series7000CircuitSP3TSwitch FunctionMom-On-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VColor - Actuator/CapBlackColor - Actuator/Cap.Ilumination Type, Color.Ilumination TypePael Mount, Snap-InMounting TypeSolder LugIngress Protection.FaturesJumper needed to achieve triple throwReal Cutout DimensionsRectangular 1.5.24mm x1.2.70mm	Category	Switches
Series7000CircuitSP3TSwitch FunctionMom-On-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeConcave (Standard V) - IlluminatedColor - Actuator/CapBlackActuator Marking.Illumination Type, Color.Illumination Voltage (Nominal).Mouting TypeSolder LugIngress ProtectionSolder LugIngress Protection.FeaturesJumpr needed to achieve triple throwPanel Cutout DimensionsKetangular - 15.24mm x 12.70mm		Rocker Switches
CircuitSP3TSwitch FunctionMom-On-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCS8VActuator TypeConcave (Standard V) - IlluminatedColor - Actuator/CapBlackActuator Marking-Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugTermination StyleSolder LugIngress Protection-FeaturesJumper Leader Staller S	Package	-
Switch FunctionMom-On-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSa VaActuator TypeConcave (Standard V) - IlluminatedColor - Actuator/CapBlackActuator Marking-Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Mount DimensionsRectangular Lug	Series	7000
Current RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeConcave (Standard V) - IlluminatedColor - Actuator/CapBlackActuator MarkingNo MarkingIllumination Type, Color-Illumination Type, Color-Mounting TypeOlder LugTermination Style-Ingress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular 12.20mm	Circuit	SP3T
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeConcave (Standard V) - IlluminatedColor - Actuator/CapBlackActuator MarkingNo MarkingIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination Style-Ingress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Switch Function	Mom-On-Mom
Voltage Rating - DC28VActuator TypeConcave (Standard V) - IlluminatedColor - Actuator/CapBlackActuator MarkingNo MarkingIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular 15.24mm x 12.70mm	Current Rating	5A (AC/DC)
Actuator TypeConcave (Standard V) - IlluminatedColor - Actuator/CapBlackActuator MarkingNo MarkingIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cuour DinnensionsRectangular 12.70mm	Voltage Rating - AC	120V
Color - Actuator/CapBlackActuator MarkingNo MarkingIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Voltage Rating - DC	28V
Actuator MarkingNo MarkingIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Actuator Type	Concave (Standard V) - Illuminated
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Color - Actuator/Cap	Black
Illumination Voltage (Nominal)-Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Actuator Marking	No Marking
Mounting TypePanel Mount, Snap-InTermination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Illumination Type, Color	-
Termination StyleSolder LugIngress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Illumination Voltage (Nominal)	-
Ingress Protection-FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Mounting Type	Panel Mount, Snap-In
FeaturesJumper needed to achieve triple throwPanel Cutout DimensionsRectangular - 15.24mm x 12.70mm	Termination Style	Solder Lug
Panel Cutout Dimensions Rectangular - 15.24mm x 12.70mm	Ingress Protection	-
	Features	Jumper needed to achieve triple throw
Report errors?	Panel Cutout Dimensions	Rectangular - 15.24mm x 12.70mm
		Report errors?

#### U215J52ZQE22 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### U215J52ZQE22 Payment Methods





If you have any question about U215J52ZQE22, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com