

U21SYZQE

U21SYZQE Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



U21SYZQE Specifications

| Manufacturer Part Number U21SYZQE Manufacturer C&K Category Switches Package - Package - Series 7000 Circuit DPDT Switch Function On-On Current Rating SA (ACDC) Voltage Rating - AC 28V Actuator Type Standard Round Actuator Length 10.67mm Illumination Non-Illuminated Illumination Type, Color - Termination Style Solder Lug Panel Cutout Dimensions Gicrular - 6.35mm Dia Bushing Thread 1/440 Ingress Protection - | | |
|--|--------------------------------|------------------------|
| Switches Toggle Switches Package - Series 000 Circuit DPDT Switch Function On-On Current Rating SA (AC/DC) Voltage Rating - AC Say Voltage Rating - DC Say Actuator Type Say Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Solder Lug Illumination Style Sale Actuature Indenduction Style Solder Lug Indenduction Style Solder Lug Indenduction Style Sale Actuature Indenduction Style Solder Lug Indenductio | Manufacturer Part Number | U21SYZQE |
| Toggle SwitchesPackage-Series7000CircuitDPDTSwitch FunctionOn-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator LengthNon-IlluminatedIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Youting TypeSolder LugTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Manufacturer | C&K |
| Package-Series700CircuitDPDTSwitch FunctionOn-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSandard RoundActuator TypeStandard RoundActuator Length1067mmIluminationNon-IluminatedIlumination Voltage (Nominal)-Mouting TypeSandard RoundIndentify SelfSolder LugMouting TypeSolder LugIndentify SelfSolder SelfSelfSolder SelfSelfSo | Category | Switches |
| Series7000CircuitDPDTSwitch FunctionOn-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSandard RoundActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fermination StyleSolder LugPanel Cutout DimensionsSolder LugBushing Thread1/440Ingress Protection-FeaturesEpsy Seaded TreminatesFeaturesEpsy Seaded Treminates | | Toggle Switches |
| CircuitDPDTSwitch FunctionOn-OnCurrent RatingSA (AC/DC)Voltage Rating - AC100VVoltage Rating - DCSavdard RoundActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fermination StyleSolder LugPanel Cutout DimensionsSolder LugBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Package | - |
| Switch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel MountSolder LugIndex SyleSolder LugPanel SyleSolder LugFamination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Series | 7000 |
| Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel MountSolder LugIndex StyleSolder LugPanel Style-Bushing Thread1/440Ingress Protection-FeaturesEpoxy Sealed Terminals | Circuit | DPDT |
| Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandar RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeStoler LugPanel Cutour DimensionsStoler LugBushing Thread1/440Ingress Protection-FeaturesEpoxy Staler Greininals | Switch Function | On-On |
| Voltage Rating - DC28VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Current Rating | 5A (AC/DC) |
| Actuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Voltage Rating - AC | 120V |
| Actuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Voltage Rating - DC | 28V |
| IluminationNon-IlluminatedIllumination Type, Color-Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Actuator Type | Standard Round |
| Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Actuator Length | 10.67mm |
| Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Illumination | Non-Illuminated |
| Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Illumination Type, Color | - |
| Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Illumination Voltage (Nominal) | - |
| Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Mounting Type | Panel Mount |
| Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Termination Style | Solder Lug |
| Ingress Protection-FeaturesEpoxy Sealed Terminals | Panel Cutout Dimensions | Circular - 6.35mm Dia |
| Features Epoxy Sealed Terminals | Bushing Thread | 1/4-40 |
| | Ingress Protection | - |
| Report errors? | Features | Epoxy Sealed Terminals |
| | | Report errors? |

U21SYZQE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

U21SYZQE Payment Methods



U21SYZQE Shipping Methods



If you have any question about U21SYZQE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com