



U21TZGE Information

Heisener.com

For Reference Only

Part NumberU21TZGEManufacturerC&KCategorySwitches

Toggle Switches

Description SWITCH TOGGLE DPDT 5A 120V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









U21TZGE Specifications

Manufacturer Part Number U21TZGE Manufacturer C&K Category Switches Package - Series 7000 Circuit DPDT Switch Function On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection -		
Category Package Series 7000 Circuit DPDT Switch Function Current Rating Voltage Rating - AC Voltage Rating - DC Actuator Type Actuator Type Actuator Length Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread Series 7000 On-On On-On On-On On-On 28V Act/DC) Volv 28V Standard Round 17.45mm Non-Illuminated Illuminated Illumination Panel Mount Termination Style Panel Mount Termination Style Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread	Manufacturer Part Number	U21TZGE
Package - Series 7000 Circuit DPDT Switch Function On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread Toggle Switches - On-On TOUT TOUT TOUT TOUT TOUT TOUT TOUT TO	Manufacturer	C&K
Package-Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32	Category	Switches
Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32		Toggle Switches
CircuitDPDTSwitch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32	Package	-
Switch Function On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32	Series	7000
Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32	Circuit	DPDT
Voltage Rating - AC Voltage Rating - DC 28V Actuator Type Standard Round 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread 120V 28V 28V Standard Round 17.45mm Non-Illuminated 17.45mm Non-Illuminated - Von-Illuminated Stongle Panel Mount Circular - 11.91mm Dia 15/32-32	Switch Function	On-On
Voltage Rating - DC Actuator Type Standard Round 17.45mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread 28V Standard Round 17.45mm Non-Illuminated	Current Rating	5A (AC/DC)
Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32	Voltage Rating - AC	120V
Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32	Actuator Type	Standard Round
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32	Actuator Length	17.45mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32	Mounting Type	Panel Mount
Bushing Thread 15/32-32	Termination Style	Solder Lug
	Panel Cutout Dimensions	Circular - 11.91mm Dia
Ingress Protection -	Bushing Thread	15/32-32
	Ingress Protection	-
Features Epoxy Sealed Terminals	Features	Epoxy Sealed Terminals
Report errors?		Report errors?

U21TZGE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

U21TZGE Payment Methods





















U21TZGE Shipping Methods













If you have any question about U21TZGE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com