



U411TZGE Information

(A) Heisener.com

Part Number U411TZGE Manufacturer C&K

Category Switches

Toggle Switches

Description SWITCH TOGGLE DP3T 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









U411TZGE Specifications

| Manufacturer Part Number U411TZGE Manufacturer C&K Category Switches Package - Scries 7000 Circuit DP3T Switch Function On-On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw | - | |
|---|--------------------------------|---------------------------------------|
| Category Switches Package - Series 7000 Circuit DP3T Switch Function On-On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw | Manufacturer Part Number | U411TZGE |
| Package - 7000 Series 7000 Circuit DP3T Switch Function On-On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw | Manufacturer | C&K |
| Package-Series7000CircuitDP3TSwitch FunctionOn-On-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesJumper needed to achieve triple throw | Category | Switches |
| Series7000CircuitDP3TSwitch FunctionOn-On-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesJumper needed to achieve triple throw | | Toggle Switches |
| CircuitDP3TSwitch FunctionOn-On-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesJumper needed to achieve triple throw | Package | - |
| Switch Function Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) Termination Style Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread Ingress Protection Features Jumper needed to achieve triple throw | Series | 7000 |
| Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesJumper needed to achieve triple throw | Circuit | DP3T |
| Voltage Rating - AC Voltage Rating - DC 28V Actuator Type Standard Round 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection Features 120V 28V 28V Standard Round 17.45mm Non-Illumination Non-Illuminated 17.45mm Non-Illuminated 17.45mm Non-Illuminated 17.45mm Non-Illuminated 17.45mm Circular - 11.91mm Dia 15/32-32 Ingress Protection Jumper needed to achieve triple throw | Switch Function | On-On-On |
| Voltage Rating - DC Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread Ingress Protection Features Jumper needed to achieve triple throw | Current Rating | 5A (AC/DC) |
| Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw | Voltage Rating - AC | 120V |
| Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw | Voltage Rating - DC | 28V |
| Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw | Actuator Type | Standard Round |
| Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw | Actuator Length | 17.45mm |
| Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw | Illumination | Non-Illuminated |
| Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw | Illumination Type, Color | - |
| Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw | Illumination Voltage (Nominal) | - |
| Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection Features Jumper needed to achieve triple throw | Mounting Type | Panel Mount |
| Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw | Termination Style | Solder Lug |
| Ingress Protection - Features Jumper needed to achieve triple throw | Panel Cutout Dimensions | Circular - 11.91mm Dia |
| Features Jumper needed to achieve triple throw | Bushing Thread | 15/32-32 |
| | Ingress Protection | - |
| Report errors? | Features | Jumper needed to achieve triple throw |
| | | Report errors? |

U411TZGE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

U411TZGE Payment Methods



















U411TZGE Shipping Methods













If you have any question about U411TZGE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com