



### **U5600-00000E-002BA Information**

Part Number U5600-00000E-002BA

Manufacturer TE Connectivity Measurement Specialties

**Category** Sensors, Transducers

Pressure Sensors, Transducers

**Description** WIRELESS PRESSURE GAUGE 30PSI

Package Cylinder, Threaded

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## U5600-00000E-002BA Specifications

| Manufacturer Part Number     U5600-0000E-002BA       Manufacturer     TE Connectivity Measurement Specialties       Category     Sensors, Transducers       Package     Cylinder, Threaded       Series     -       Pressure Type     Absolute       Operating Pressure     29.01 PSI (200 kPa)       Output Type     Bluetooth       Output     24 b       Accuracy     ±0.1%       Voltage - Supply     2.3 V ~ 3.6 V       Port Size     Male - 1/4" (6.35mm) BSPT       Port Style     Threaded       Features     Temperature Compensated       Termination Style     -       Maximum Pressure     87.02 PSI (600 kPa)       Operating Temperature     -20°C ~ 85°C       Package / Case     Cylinder, Threaded       Supplier Device Package     -       Report errors?  |                          |   |
|--|--------------------------|---|
| Category Sensors, Transducers Pressure Sensors, Transducers  Package Cylinder, Threaded Series - Pressure Type Absolute Operating Pressure Operating Pressure Bluetooth Output Type Bluetooth Output 24 b Accuracy ±0.1% Voltage - Supply 2.3 V ~ 3.6 V Port Size Male - 1/4" (6.35mm) BSPT Port Style Features Temperature Compensated Termination Style  Maximum Pressure 87.02 PSI (600 kPa) Operating Temperature - 20°C ~ 85°C Package / Case Supplier Device Package -   | Manufacturer Part Number | U5600-00000E-002BA                      |
| Package Cylinder, Threaded Series - Pressure Type Absolute Operating Pressure Output Type Bluetooth Output Accuracy ±0.1% Voltage - Supply 2.3 V ~ 3.6 V Port Size Male - 1/4" (6.35mm) BSPT Port Style Threaded Features Tempination Style Termination Style Maximum Pressure Operating Temperature Port Case Supplier Device Package  Pressure Sensors, Transducers Cylinder, Threaded  Cylinder, Threaded Features Cylinder, Threaded Features Feature Compensated Features Featu    | Manufacturer             | TE Connectivity Measurement Specialties |
| PackageCylinder, ThreadedSeries-Pressure TypeAbsoluteOperating Pressure29.01 PSI (200 kPa)Output TypeBluetoothOutput24 bAccuracy±0.1%Voltage - Supply2.3 V ~ 3.6 VPort SizeMale - 1/4" (6.35mm) BSPTPort StyleThreadedFeaturesTemperature CompensatedTermination Style-Maximum Pressure87.02 PSI (600 kPa)Operating Temperature-20°C ~ 85°CPackage / CaseCylinder, ThreadedSupplier Device Package-  | Category                 | Sensors, Transducers                    |
| Series         -           Pressure Type         Absolute           Operating Pressure         29.01 PSI (200 kPa)           Output Type         Bluetooth           Output         24 b           Accuracy         ±0.1%           Voltage - Supply         2.3 V ~ 3.6 V           Port Size         Male - 1/4" (6.35mm) BSPT           Port Style         Threaded           Features         Temperature Compensated           Termination Style         -           Maximum Pressure         87.02 PSI (600 kPa)           Operating Temperature         -20°C ~ 85°C           Package / Case         Cylinder, Threaded           Supplier Device Package         -  |                          | Pressure Sensors, Transducers           |
| Pressure Type Absolute Operating Pressure 29.01 PSI (200 kPa) Output Type Bluetooth Output Accuracy ±0.1% Voltage - Supply 2.3 V ~ 3.6 V Port Size Male - 1/4" (6.35mm) BSPT Port Style Threaded Features Temperature Compensated Termination Style - Maximum Pressure 87.02 PSI (600 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package  | Package                  | Cylinder, Threaded                      |
| Operating Pressure  Output Type  Bluetooth  Output  24 b  Accuracy  ±0.1%  Voltage - Supply  Port Size  Male - 1/4" (6.35mm) BSPT  Port Style  Threaded  Features  Temperature Compensated  Termination Style  Aximum Pressure  87.02 PSI (600 kPa)  Operating Temperature  -20°C ~ 85°C  Package / Case  Supplier Device Package  -  29.01 PSI (200 kPa)  Bluetooth  24 b  ### Canada  ## | Series                   | -                                       |
| Output TypeBluetoothOutput24 bAccuracy±0.1%Voltage - Supply2.3 V ~ 3.6 VPort SizeMale - 1/4" (6.35mm) BSPTPort StyleThreadedFeaturesTemperature CompensatedTermination Style-Maximum Pressure87.02 PSI (600 kPa)Operating Temperature-20°C ~ 85°CPackage / CaseCylinder, ThreadedSupplier Device Package-  | Pressure Type            | Absolute                                |
| Output 24 b  Accuracy ±0.1%  Voltage - Supply 2.3 V ~ 3.6 V  Port Size Male - 1/4" (6.35mm) BSPT  Port Style Threaded  Features Temperature Compensated  Termination Style -  Maximum Pressure 87.02 PSI (600 kPa)  Operating Temperature - 20°C ~ 85°C  Package / Case Cylinder, Threaded  Supplier Device Package -  | Operating Pressure       | 29.01 PSI (200 kPa)                     |
| Accuracy ±0.1%  Voltage - Supply 2.3 V ~ 3.6 V  Port Size Male - 1/4" (6.35mm) BSPT  Port Style Threaded  Features Temperature Compensated  Termination Style -  Maximum Pressure 87.02 PSI (600 kPa)  Operating Temperature -20°C ~ 85°C  Package / Case Cylinder, Threaded  Supplier Device Package -  | Output Type              | Bluetooth                               |
| Voltage - Supply  2.3 V ~ 3.6 V  Port Size  Male - 1/4" (6.35mm) BSPT  Port Style  Threaded  Features  Temperature Compensated  Termination Style  -  Maximum Pressure  87.02 PSI (600 kPa)  Operating Temperature  -20°C ~ 85°C  Package / Case  Cylinder, Threaded  Supplier Device Package  -   | Output                   | 24 b                                    |
| Port Size Male - 1/4" (6.35mm) BSPT  Port Style Threaded  Features Temperature Compensated  Termination Style -  Maximum Pressure 87.02 PSI (600 kPa)  Operating Temperature -20°C ~ 85°C  Package / Case Cylinder, Threaded  Supplier Device Package -  | Accuracy                 | ±0.1%                                   |
| Port Style Threaded  Features Temperature Compensated  Termination Style -  Maximum Pressure 87.02 PSI (600 kPa)  Operating Temperature -20°C ~ 85°C  Package / Case Cylinder, Threaded  Supplier Device Package -   | Voltage - Supply         | 2.3 V ~ 3.6 V                           |
| Features Temperature Compensated  Termination Style  | Port Size                | Male - 1/4" (6.35mm) BSPT               |
| Termination Style -  Maximum Pressure 87.02 PSI (600 kPa)  Operating Temperature -20°C ~ 85°C  Package / Case Cylinder, Threaded  Supplier Device Package -  | Port Style               | Threaded                                |
| Maximum Pressure87.02 PSI (600 kPa)Operating Temperature-20°C ~ 85°CPackage / CaseCylinder, ThreadedSupplier Device Package-   | Features                 | Temperature Compensated                 |
| Operating Temperature -20°C ~ 85°C  Package / Case Cylinder, Threaded  Supplier Device Package -   | Termination Style        | -                                       |
| Package / Case Cylinder, Threaded Supplier Device Package -  | Maximum Pressure         | 87.02 PSI (600 kPa)                     |
| Supplier Device Package -  | Operating Temperature    | -20°C ~ 85°C                            |
|  | Package / Case           | Cylinder, Threaded                      |
| Report errors?   | Supplier Device Package  | -                                       |
|  |                          | Report errors?                          |

#### **U5600-00000E-002BA Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## U5600-00000E-002BA Payment Methods





















### U5600-00000E-002BA Shipping Methods













If you have any question about U5600-00000E-002BA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com