



### **UAL10-20KF8 Information**

www

For Reference Only

Part Number UAL10-20KF8

Manufacturer Riedon
Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 20K OHM 1% 10W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **UAL10-20KF8 Specifications**

Manufacturer Part NumberUAL10-20KF8ManufacturerRiedonCategoryResistorsPackageAxial, BoxSeriesUALResistance20 kOhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.752" L x 0.799" W (19.10mm x 20.30mm)Height - Seated (Max)0.417" (10.60mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-Report errors?		
CategoryResistorsPackageAxial, BoxSeriesUALResistance20 kOhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.752" L x 0.799" W (19.10mm x 20.30mm)Height - Seated (Max)0.417" (10.60mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer Part Number	UAL10-20KF8
Chassis Mount Resistors  Package Axial, Box  UAL  Resistance 20 kOhms  Tolerance ±1%  Power (Watts) 10W  Composition Wirewound  Temperature Coefficient ±20pm/°C  Operating Temperature -55°C ~ 275°C  Features Moisture Resistant, Pulse Withstanding  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm)  Height - Seated (Max) 0.417" (10.60mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate	Manufacturer	Riedon
PackageAxial, BoxSeriesUALResistance20 kOhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.752" L x 0.799" W (19.10mm x 20.30mm)Height - Seated (Max)0.417" (10.60mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesUALResistance20 kOhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.752" L x 0.799" W (19.10mm x 20.30mm)Height - Seated (Max)0.417" (10.60mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance20 kOhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.752" L x 0.799" W (19.10mm x 20.30mm)Height - Seated (Max)0.417" (10.60mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance ±1%  Power (Watts) 10W  Composition Wirewound  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 275°C  Features Moisture Resistant, Pulse Withstanding  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm)  Height - Seated (Max) 0.417" (10.60mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Series	UAL
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±20ppm/°C  Operating Temperature  -55°C ~ 275°C  Features  Moisture Resistant, Pulse Withstanding  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.752" L x 0.799" W (19.10mm x 20.30mm)  Height - Seated (Max)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  -	Resistance	20 kOhms
Composition  Wirewound  temperature Coefficient  begin{align*} 20ppm/°C  Departing Temperature  costing, Temperature  begin{align*} 55°C ~ 275°C  Moisture Resistant, Pulse Withstanding  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  continued  begin{align*} 0.752" L x 0.799" W (19.10mm x 20.30mm)  continued  begin{align*} 0.417" (10.60mm)  continued  c	Tolerance	±1%
Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 275°C  Features Moisture Resistant, Pulse Withstanding  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm)  Height - Seated (Max) 0.417" (10.60mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Power (Watts)	10W
Operating Temperature  -55°C ~ 275°C  Features  Moisture Resistant, Pulse Withstanding  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.752" L x 0.799" W (19.10mm x 20.30mm)  Height - Seated (Max)  0.417" (10.60mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  -	Composition	Wirewound
Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm) Height - Seated (Max) 0.417" (10.60mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±20ppm/°C
Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.752" L x 0.799" W (19.10mm x 20.30mm)  Height - Seated (Max)  0.417" (10.60mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  -	Operating Temperature	-55°C ~ 275°C
Mounting Feature  Size / Dimension  O.752" L x 0.799" W (19.10mm x 20.30mm)  Height - Seated (Max)  Lead Style  Package / Case  Axial, Box  Failure Rate  Flanges  O.417" (10.60mm)  Solder Lugs  Axial, Box	Features	Moisture Resistant, Pulse Withstanding
Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm)  Height - Seated (Max) 0.417" (10.60mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max)  Lead Style  Package / Case  Axial, Box  Failure Rate  0.417" (10.60mm)  Solder Lugs  -	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	0.752" L x 0.799" W (19.10mm x 20.30mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.417" (10.60mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

#### **UAL10-20KF8 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **UAL10-20KF8 Payment Methods**



















## **UAL10-20KF8 Shipping Methods**













If you have any question about UAL10-20KF8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com