

UAL10-25RF8 Information

w. om

For Reference Only

Part Number UAL10-25RF8

Manufacturer Riedon
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 25 OHM 1% 10W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UAL10-25RF8 Specifications

Manufacturer Part Number UAL10-25RF8 Manufacturer Riedon Category Resistors Package Axial, Box Series UAL Resistance 25 Ohms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm) Height - Seated (Max) 0.417" (10.60mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -		
CategoryResistorsPackageAxial, BoxSeriesUALResistance25 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.752" L x 0.799" W (19.10mm x 20.30mm)Height - Seated (Max)0.417" (10.60mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer Part Number	UAL10-25RF8
Chassis Mount Resistors Package Axial, Box UAL Resistance 25 Ohms Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm) Height - Seated (Max) 0.417" (10.60mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Manufacturer	Riedon
PackageAxial, BoxSeriesUALResistance25 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.752" L x 0.799" W (19.10mm x 20.30mm)Height - Seated (Max)0.417" (10.60mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesUALResistance25 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.752" L x 0.799" W (19.10mm x 20.30mm)Height - Seated (Max)0.417" (10.60mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance25 OhmsTolerance±1%Power (Watts)10WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.752" L x 0.799" W (19.10mm x 20.30mm)Height - Seated (Max)0.417" (10.60mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance ±1% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm) Height - Seated (Max) 0.417" (10.60mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Series	UAL
Power (Watts) Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Resistance	25 Ohms
Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm) Height - Seated (Max) 0.417" (10.60mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Tolerance	±1%
Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm) Height - Seated (Max) 0.417" (10.60mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Power (Watts)	10W
Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm) Height - Seated (Max) 0.417" (10.60mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Composition	Wirewound
Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm) Height - Seated (Max) 0.417" (10.60mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±20ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm) Height - Seated (Max) 0.417" (10.60mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Operating Temperature	-55°C ~ 275°C
Mounting Feature Flanges 0.752" L x 0.799" W (19.10mm x 20.30mm) Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate Flanges 0.417" (10.60mm) Solder Lugs Axial, Box	Features	Moisture Resistant, Pulse Withstanding
Size / Dimension 0.752" L x 0.799" W (19.10mm x 20.30mm) Height - Seated (Max) 0.417" (10.60mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	0.752" L x 0.799" W (19.10mm x 20.30mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.417" (10.60mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

UAL10-25RF8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UAL10-25RF8 Payment Methods





















UAL10-25RF8 Shipping Methods













If you have any question about UAL10-25RF8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com