



### **UAL5-15RF8 Information**

Part Number UAL5-15RF8

Manufacturer Riedon Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 15 OHM 1% 7.5W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **UAL5-15RF8 Specifications**

Manufacturer Part Number         UAL5-15RF8           Manufacturer         Riedon           Category         Resistors           Package         Axial, Box           Series         UAL           Resistance         15 Ohms           Tolerance         ±1%           Power (Watts)         7.5W           Composition         Wirewound           Temperature Coefficient         ±20ppm/°C           Operating Temperature         -55°C ~ 275°C           Features         Moisture Resistant, Pulse Withstanding           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         0.598" L x 0.646" W (15.20mm x 16.40mm)           Height - Seated (Max)         0.335" (8.50mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box           Failure Rate         -		
CategoryResistorsPackageAxial, BoxSeriesUALResistance15 OhmsTolerance±1%Power (Watts)7.5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.598" L x 0.646" W (15.20mm x 16.40mm)Height - Seated (Max)0.335" (8.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer Part Number	UAL5-15RF8
Chassis Mount Resistors  Package Axial, Box UAL Resistance 15 Ohms  Tolerance ±1% Power (Watts) 7.5W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate	Manufacturer	Riedon
PackageAxial, BoxSeriesUALResistance15 OhmsTolerance±1%Power (Watts)7.5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.598" L x 0.646" W (15.20mm x 16.40mm)Height - Seated (Max)0.335" (8.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesUALResistance15 OhmsTolerance±1%Power (Watts)7.5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.598" L x 0.646" W (15.20mm x 16.40mm)Height - Seated (Max)0.335" (8.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance15 OhmsTolerance±1%Power (Watts)7.5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.598" L x 0.646" W (15.20mm x 16.40mm)Height - Seated (Max)0.335" (8.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance ±1%  Power (Watts) 7.5W  Composition Wirewound  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 275°C  Features Moisture Resistant, Pulse Withstanding  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm)  Height - Seated (Max) 0.335" (8.50mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Series	UAL
Power (Watts)  Composition  Wirewound  Temperature Coefficient  ±20ppm/°C  Operating Temperature  -55°C ~ 275°C  Features  Moisture Resistant, Pulse Withstanding  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.598" L x 0.646" W (15.20mm x 16.40mm)  Height - Seated (Max)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  -	Resistance	15 Ohms
Composition Wirewound  Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 275°C  Features Moisture Resistant, Pulse Withstanding  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm)  Height - Seated (Max) 0.335" (8.50mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Tolerance	$\pm 1\%$
Temperature Coefficient ±20ppm/°C  Operating Temperature -55°C ~ 275°C  Features Moisture Resistant, Pulse Withstanding  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm)  Height - Seated (Max) 0.335" (8.50mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Power (Watts)	7.5W
Operating Temperature  -55°C ~ 275°C  Features  Moisture Resistant, Pulse Withstanding  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.598" L x 0.646" W (15.20mm x 16.40mm)  Height - Seated (Max)  0.335" (8.50mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  -	Composition	Wirewound
Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm) Height - Seated (Max) 0.335" (8.50mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±20ppm/°C
Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  0.598" L x 0.646" W (15.20mm x 16.40mm)  Height - Seated (Max)  0.335" (8.50mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  -	Operating Temperature	-55°C ~ 275°C
Mounting Feature  Size / Dimension  O.598" L x 0.646" W (15.20mm x 16.40mm)  Height - Seated (Max)  Lead Style  Package / Case  Axial, Box  Failure Rate  Flanges  O.598" L x 0.646" W (15.20mm x 16.40mm)  Axial, Box  -	Features	Moisture Resistant, Pulse Withstanding
Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm)  Height - Seated (Max) 0.335" (8.50mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max)  Lead Style  Package / Case  Failure Rate  0.335" (8.50mm)  Solder Lugs  Axial, Box  -	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	0.598" L x 0.646" W (15.20mm x 16.40mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.335" (8.50mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
	Failure Rate	-
Report errors?		Report errors?

### **UAL5-15RF8** Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **UAL5-15RF8 Payment Methods**



















### **UAL5-15RF8 Shipping Methods**













If you have any question about UAL5-15RF8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com