

UAL5-50RF8 Information

Part Number UAL5-50RF8

ManufacturerRiedonCategoryResistors

Chassis Mount Resistors

Description RES CHAS MNT 50 OHM 1% 7.5W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UAL5-50RF8 Specifications

Manufacturer Part Number UAL5-50RF8 Manufacturer Riedon Category Resistors Package Axial, Box Series UAL Resistance 50 Ohms Tolerance ±1% Power (Watts) 7.5W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm) Height - Seated (Max) 0.335" (8.50mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -			
CategoryResistorsPackageAxial, BoxSeriesUALResistance50 OhmsTolerance±1%Power (Watts)7.5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.598" L x 0.646" W (15.20mm x 16.40mm)Height - Seated (Max)0.335" (8.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer Part Number	UAL5-50RF8	
Chassis Mount Resistors Package Axial, Box UAL Resistance 50 Ohms Tolerance ±1% Power (Watts) 7.5W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm) Height - Seated (Max) 0.335" (8.50mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Manufacturer	Riedon	
PackageAxial, BoxSeriesUALResistance50 OhmsTolerance±1%Power (Watts)7.5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.598" L x 0.646" W (15.20mm x 16.40mm)Height - Seated (Max)0.335" (8.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors	
SeriesUALResistance50 OhmsTolerance±1%Power (Watts)7.5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.598" L x 0.646" W (15.20mm x 16.40mm)Height - Seated (Max)0.335" (8.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors	
Resistance50 OhmsTolerance±1%Power (Watts)7.5WCompositionWirewoundTemperature Coefficient±20ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension0.598" L x 0.646" W (15.20mm x 16.40mm)Height - Seated (Max)0.335" (8.50mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box	
Tolerance ±1% Power (Watts) 7.5W Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm) Height - Seated (Max) 0.335" (8.50mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Series	UAL	
Power (Watts) 7.5W Composition Wirewound ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm) Height - Seated (Max) 1.20	Resistance	50 Ohms	
Composition Wirewound Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm) Height - Seated (Max) 0.335" (8.50mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Tolerance	±1%	
Temperature Coefficient ±20ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm) Height - Seated (Max) 0.335" (8.50mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Power (Watts)	7.5W	
Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm) Height - Seated (Max) 0.335" (8.50mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Composition	Wirewound	
Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm) Height - Seated (Max) 0.335" (8.50mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±20ppm/°C	
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm) Height - Seated (Max) 0.335" (8.50mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Operating Temperature	-55°C ~ 275°C	
Mounting Feature Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm) Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate Flanges 0.598" L x 0.646" W (15.20mm x 16.40mm) Axial, Box -	Features	Moisture Resistant, Pulse Withstanding	
Size / Dimension 0.598" L x 0.646" W (15.20mm x 16.40mm) Height - Seated (Max) 0.335" (8.50mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum	
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate	Mounting Feature	Flanges	
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	0.598" L x 0.646" W (15.20mm x 16.40mm)	
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.335" (8.50mm)	
Failure Rate -	Lead Style	Solder Lugs	
	Package / Case	Axial, Box	
Report errors?	Failure Rate	-	
		Report error	s?

UAL5-50RF8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UAL5-50RF8 Payment Methods



















UAL5-50RF8 Shipping Methods













If you have any question about UAL5-50RF8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com