

UAL50-5RF8 Information



For Reference Only

Part Number UAL50-5RF8

Manufacturer Riedon
Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 5 OHM 1% 50W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UAL50-5RF8 Specifications

Manufacturer Part Number UAL50-5RF8 Manufacturer Riedon Category Resistors Package Axial, Box Series UAL Resistance 5 Ohms Tolerance ±1% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm) Height - Seated (Max) 0.630" (16.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -		
CategoryResistorsPackageAxial, BoxSeriesUALResistance5 OhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.969" L x 1.142" W (50.00mm x 29.00mm)Height - Seated (Max)0.630" (16.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer Part Number	UAL50-5RF8
Chassis Mount Resistors Package Axial, Box UAL Resistance 5 Ohms Tolerance ±1% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm) Height - Seated (Max) 0.630" (16.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate	Manufacturer	Riedon
PackageAxial, BoxSeriesUALResistance5 OhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.969" L x 1.142" W (50.00mm x 29.00mm)Height - Seated (Max)0.630" (16.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesUALResistance5 OhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.969" L x 1.142" W (50.00mm x 29.00mm)Height - Seated (Max)0.630" (16.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance5 OhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.969" L x 1.142" W (50.00mm x 29.00mm)Height - Seated (Max)0.630" (16.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance ±1% Power (Watts) 50W Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm) Height - Seated (Max) 0.630" (16.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Series	UAL
Power (Watts) Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Resistance	5 Ohms
Composition Wirewound Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm) Height - Seated (Max) 0.630" (16.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Tolerance	±1%
Temperature Coefficient ±50ppm/°C Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm) Height - Seated (Max) 0.630" (16.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Power (Watts)	50W
Operating Temperature -55°C ~ 275°C Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm) Height - Seated (Max) 0.630" (16.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Composition	Wirewound
Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm) Height - Seated (Max) 0.630" (16.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±50ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm) Height - Seated (Max) 0.630" (16.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Operating Temperature	-55°C ~ 275°C
Mounting Feature Flanges Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm) Height - Seated (Max) 0.630" (16.00mm) Lead Style Package / Case Axial, Box Failure Rate -	Features	Moisture Resistant, Pulse Withstanding
Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm) Height - Seated (Max) 0.630" (16.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Axial, Box Failure Rate	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	1.969" L x 1.142" W (50.00mm x 29.00mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.630" (16.00mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

UAL50-5RF8 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UAL50-5RF8 Payment Methods

































If you have any question about UAL50-5RF8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com