

## **UAL50-6RF8 Information**



For Reference Only

Part Number UAL50-6RF8

Manufacturer Riedon
Category Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 6 OHM 1% 50W

Package Axial, Box

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **UAL50-6RF8 Specifications**

Manufacturer Part Number         UAL50-6RF8           Manufacturer         Riedon           Category         Resistors           Chassis Mount Resistors           Package         Axial, Box           Series         UAL           Resistance         6 Ohms           Tolerance         ±1%           Power (Watts)         50W           Composition         Wirewound           Temperature Coefficient         ±50ppm/°C           Operating Temperature         -55°C ~ 275°C           Features         Moisture Resistant, Pulse Withstanding           Coating, Housing Type         Aluminum           Mounting Feature         Flanges           Size / Dimension         1.969" L x 1.142" W (50.00mm x 29.00mm)           Height - Seated (Max)         0.630" (16.00mm)           Lead Style         Solder Lugs           Package / Case         Axial, Box           Failure Rate         -		
CategoryResistorsPackageAxial, BoxSeriesUALResistance6 OhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.969" L x 1.142" W (50.00mm x 29.00mm)Height - Seated (Max)0.630" (16.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Manufacturer Part Number	UAL50-6RF8
Chassis Mount Resistors  Package Axial, Box  UAL  Resistance 6 Ohms  Tolerance ±1%  Power (Watts) 50W  Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 275°C  Features Moisture Resistant, Pulse Withstanding  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.969° L x 1.142° W (50.00mm x 29.00mm)  Height - Seated (Max) 0.630° (16.00mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate	Manufacturer	Riedon
PackageAxial, BoxSeriesUALResistance6 OhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.969" L x 1.142" W (50.00mm x 29.00mm)Height - Seated (Max)0.630" (16.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Category	Resistors
SeriesUALResistance6 OhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.969" L x 1.142" W (50.00mm x 29.00mm)Height - Seated (Max)0.630" (16.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-		Chassis Mount Resistors
Resistance6 OhmsTolerance±1%Power (Watts)50WCompositionWirewoundTemperature Coefficient±50ppm/°COperating Temperature-55°C ~ 275°CFeaturesMoisture Resistant, Pulse WithstandingCoating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension1.969" L x 1.142" W (50.00mm x 29.00mm)Height - Seated (Max)0.630" (16.00mm)Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Package	Axial, Box
Tolerance ±1%  Power (Watts) 50W  Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 275°C  Features Moisture Resistant, Pulse Withstanding  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm)  Height - Seated (Max) 0.630" (16.00mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Series	UAL
Power (Watts) 50W  Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 275°C  Features Moisture Resistant, Pulse Withstanding  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm)  Height - Seated (Max) 0.630" (16.00mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Resistance	6 Ohms
Composition Wirewound  Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 275°C  Features Moisture Resistant, Pulse Withstanding  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm)  Height - Seated (Max) 0.630" (16.00mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Tolerance	±1%
Temperature Coefficient ±50ppm/°C  Operating Temperature -55°C ~ 275°C  Features Moisture Resistant, Pulse Withstanding  Coating, Housing Type Aluminum  Mounting Feature Flanges  Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm)  Height - Seated (Max) 0.630" (16.00mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Power (Watts)	50W
Operating Temperature  -55°C ~ 275°C  Features  Moisture Resistant, Pulse Withstanding  Coating, Housing Type  Aluminum  Mounting Feature  Flanges  Size / Dimension  1.969" L x 1.142" W (50.00mm x 29.00mm)  Height - Seated (Max)  0.630" (16.00mm)  Lead Style  Solder Lugs  Package / Case  Axial, Box  Failure Rate  -	Composition	Wirewound
Features Moisture Resistant, Pulse Withstanding Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm) Height - Seated (Max) 0.630" (16.00mm) Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Temperature Coefficient	±50ppm/°C
Coating, Housing Type Aluminum  Mounting Feature Flanges Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm) Height - Seated (Max) 0.630" (16.00mm)  Lead Style Solder Lugs Package / Case Axial, Box Failure Rate -	Operating Temperature	-55°C ~ 275°C
Mounting Feature  Size / Dimension  1.969" L x 1.142" W (50.00mm x 29.00mm)  Height - Seated (Max)  0.630" (16.00mm)  Lead Style  Package / Case  Axial, Box  Failure Rate  -	Features	Moisture Resistant, Pulse Withstanding
Size / Dimension 1.969" L x 1.142" W (50.00mm x 29.00mm)  Height - Seated (Max) 0.630" (16.00mm)  Lead Style Solder Lugs  Package / Case Axial, Box  Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max)  Lead Style  Package / Case  Axial, Box  Failure Rate	Mounting Feature	Flanges
Lead StyleSolder LugsPackage / CaseAxial, BoxFailure Rate-	Size / Dimension	1.969" L x 1.142" W (50.00mm x 29.00mm)
Package / Case Axial, Box Failure Rate -	Height - Seated (Max)	0.630" (16.00mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Axial, Box
Report errors?	Failure Rate	-
		Report errors?

### **UAL50-6RF8** Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UAL50-6RF8 Payment Methods**





















### **UAL50-6RF8 Shipping Methods**













If you have any question about UAL50-6RF8, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com