

#### **UB2-4.5NUN-L Information**

Part Number UB2-4.5NUN-L

Manufacturer KEMET Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE DPDT 1A 4.5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

nttps://www.neisener.com

Request a Quote



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **UB2-4.5NUN-L Specifications**

Manufacturer Part Number  Manufacturer  KEMET  Category  Relays  Signal Relays, Up to 2 Amps  Package  - Series  UB2  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  31mA  Coil Voltage  4.5VDC  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  1A  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  Ims  Features  Mounting Type  Gull Wing  Report errors?		
CategoryRelaysPackage-SeriesUB2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current31mACoil Voltage4.5 VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)0.45 VDCOperate Time2msRelease Time1msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	UB2-4.5NUN-L
Package - Series UB2 Relay Type General Purpose Coil Type Non Latching Coil Current 31mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style General Purpose 1Ba UB2 General Purpose LB2 General Purpose LB2 General Purpose LB2 SovAC, 220VDC - Max 1 mA  ImA Switching Voltage (Max) 3.38 VDC ImB Surface Mount Turn Off Voltage (Min) 0.45 VDC Operate Time 1ms Features - Guil Wing	Manufacturer	KEMET
Package - Beries UB2 Relay Type General Purpose General Purpose Non Latching Coil Type Non Latching Coil Current 31mA Coil Voltage 4.5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style General Purpose Surface Mount	Category	Relays
SeriesUB2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current31mACoil Voltage4.5 VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)0.45 VDCOperate Time2msRelease TimeImsFeatures-Mounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current31mACoil Voltage4.5 VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)0.45 VDCOperate Time2msRelease Time1msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil TypeNon LatchingCoil Current31mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.38 VDCTurn Off Voltage (Min)0.45 VDCOperate Time2msRelease Time1msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Series	UB2
Coil Current Coil Voltage 4.5 VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 2ms Release Time Ims Features - Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	General Purpose
Coil Voltage 4.5VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 1A  Switching Voltage 250VAC, 220VDC - Max  Turn On Voltage (Max) 3.38 VDC  Turn Off Voltage (Min) 0.45 VDC  Operate Time 2ms  Release Time 1ms  Features	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  3.38 VDC  Turn Off Voltage (Min)  0.45 VDC  Operate Time  2ms  Release Time  Ims  Features  -  Mounting Type  Surface Mount  Termination Style  DPDT (2 Form C)  1A  1A  250VAC, 220VDC - Max  3.38 VDC	Coil Current	31mA
Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  3.38 VDC  Turn Off Voltage (Min)  0.45 VDC  Operate Time  2ms  Release Time  1ms  Features  -  Mounting Type  Surface Mount  Termination Style  Gull Wing	Coil Voltage	4.5VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.38 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 2ms Release Time 1ms Features Mounting Type Surface Mount Termination Style Gull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  Ims  Features  Mounting Type  Surface Mount  Termination Style  3.38 VDC  0.45 VDC  2ms  Lms  Features  Gull Wing	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Switching Voltage	250VAC, 220VDC - Max
Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn On Voltage (Max)	3.38 VDC
Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	0.45 VDC
Features - Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	2ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	1ms
Termination Style Gull Wing	Features	-
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
		Report errors?

#### **UB2-4.5NUN-L Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **UB2-4.5NUN-L Payment Methods**



















### **UB2-4.5NUN-L Shipping Methods**













If you have any question about UB2-4.5NUN-L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com