

UB2-5NEN Information

www.helsener.com

Part Number UB2-5NEN
Manufacturer KEMET
Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 1A 5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UB2-5NEN Specifications

Manufacturer Part Number Manufacturer KEMET Relays Signal Relays, Up to 2 Amps Package Series UB2 Relay Type General Purpose Coil Type Non Latching Coil Current 20mA Coil Voltage SvDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 2ms Release Time Ims Features Mounting Type Surface Mount Termination Style KEMET KEMET KEMET AMBER Signal Relays UB2 Amps Coll vol 2 Amps Amps Signal Relays Librat Separat Librat Librat Report errors?		
CategoryRelaysPackage-SeriesUB2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time2msRelease Time1msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	UB2-5NEN
Package-SeriesUB2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time2msRelease TimeImsFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer	KEMET
Package-SeriesUB2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time2msRelease TimeImsFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Category	Relays
SeriesUB2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time2msRelease TimeImsFeatures-Mounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time2msRelease TimeImsFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil TypeNon LatchingCoil Current20mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time2msRelease TimeImsFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Series	UB2
Coil Current Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 2ms Release Time 1ms Features Mounting Type Surface Mount Termination Style Gull Wing	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 2ms Release Time Ims Features - Mounting Type Surface Mount Termination Style DPDT (2 Form C) 1A 1A 250VAC, 220VDC - Max 3.75 VDC 1.50 VDC 0.5 VDC 0.5 VDC Cms 4 Contact Rating (Current) 1 Max 2 ms 4 Contact Rating (Current) 1 Max 5 VDC Contact Rating (Current) 6 Voltage (Max) 6 Unity Contact Rating (Current) 6 Voltage (Max) 6 Unity Contact Rating (Current) 7 Voltage (Max) 6 Unity Contact Rating (Current) 7 Voltage (Max) 8 Out Contact Rating (Current) 8 Out Contact Rating (Current) 9 Out Contact Rating (Current	Coil Current	20mA
Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Coil Voltage	5VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 2ms Release Time 1ms Features Mounting Type Surface Mount Termination Style Gull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Ims Features Mounting Type Surface Mount Termination Style 3.75 VDC 2ms Lims Surface Mount Gull Wing	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Switching Voltage	250VAC, 220VDC - Max
Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn On Voltage (Max)	3.75 VDC
Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	0.5 VDC
Features - Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	2ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	1ms
Termination Style Gull Wing	Features	-
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
		Report errors?

UB2-5NEN Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UB2-5NEN Payment Methods





















UB2-5NEN Shipping Methods













If you have any question about UB2-5NEN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com