



UBT1C222MHD Information



For Reference Only

Part Number UBT1C222MHD

Manufacturer Nichicon Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 2200UF 20% 16V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UBT1C222MHD Specifications

Manufacturer Part Number UBTIC222MHD Manufacturer Nichicon Category Capacitors Package Radial, Can Series UBT Capacitance 2200µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 125°C Operating Temperature +40°C ~ 125°C Polarization Automotive Ripple Current - Low Frequency 1.541A @ 120Hz Ripple Current - High Frequency 2.3A @ 100kHz Impedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UBT Capacitance 2200µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency 1.541A @ 120Hz Ripple Current - High Frequency 1.541A @ 100kHz Impedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	UBT1C222MHD
Package Radial, Can Series UBT Capacitance 2200μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 1.541A @ 120Hz Ripple Current - High Frequency 2.3A @ 100kHz Impedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Nichicon
Package Radial, Can Series UBT Capacitance 2200µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 1.541A @ 120Hz Ripple Current - High Frequency 2.3A @ 100kHz Impedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series UBT Capacitance 2200µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 1.541A @ 120Hz Ripple Current - High Frequency 2.3A @ 100kHz Impedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 2200μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 1.541A @ 120Hz Ripple Current - High Frequency 2.3A @ 100kHz Impedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 10000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 1.541A @ 120Hz Ripple Current - High Frequency 2.3A @ 100kHz Impedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UBT
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 1.541A @ 120Hz Rippedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can	Capacitance	2200μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 125°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 1.541A @ 120Hz Ripple Current - High Frequency 2.3A @ 100kHz Impedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 125°C Polarization Polar Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 1.541A @ 120Hz Rippedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1.0000 Hrs @ 125°C -40°C ~ 125°	Voltage - Rated	16V
Operating Temperature -40°C ~ 125°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 1.541A @ 120Hz Ripple Current - High Frequency 2.3A @ 100kHz Impedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications Automotive Ripple Current - Low Frequency 1.541A @ 120Hz Ripple Current - High Frequency 2.3A @ 100kHz Impedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	10000 Hrs @ 125°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency 2.3A @ 100kHz Impedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 125°C
Ripple Current - Low Frequency Ripple Current - High Frequency 2.3A @ 100kHz Impedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency 2.3A @ 100kHz Impedance 24 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	Automotive
Impedance24 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	1.541A @ 120Hz
Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	2.3A @ 100kHz
Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	24 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UBT1C222MHD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UBT1C222MHD Payment Methods



















UBT1C222MHD Shipping Methods













If you have any question about UBT1C222MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com