

# UBT2C151MHD

## **UBT2C151MHD Information**

theisenet.com	Part Number Manufacturer Category Description Package	Capacitors Aluminum Electrolytic Capacitors CAP ALUM 150UF 20% 160V RADIAL Radial, Can For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **UBT2C151MHD Specifications**

ManufacturerNichiconCapacitorsCapacitorsPackageRadial, CanPackageRadial, CanSeriesUBTCapacitance150µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature40°C ~ 125°CPolarizationAutomotiveRipple Current - High Frequency434mA @ 120HzRipple Current - High Frequency651mA @ 100kHzSize / Dimension0.295° (7.50mm)Size / Dimension1.319° (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila, Can	_	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageUBTCapacitance150µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationAutomotiveRipple Current - Low Frequency434mA @ 120HzRipple Current - High Frequency651mA @ 100kHzImpedance-Lied Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.319° (33.50mm)Surface Mount Land Size-Package / CaseRatio, Can	Manufacturer Part Number	UBT2C151MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUBTCapacitance150µFTolerance±20%Voltage - Rated60VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature40°C ~ 125°CPolarizationAutomotiveRipple Current - Low Frequency434mA @ 120HzRipple Current - High Frequency651mA @ 100kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.319° (33.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUBTCapacitance150µFTolerance±20%Voltage - Rated60VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature40°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency651mA @ 100kHzRipple Current - High Frequency651mA @ 100kHzSize / Dimension0.295° (7.50mm)Size / Dimension1.319° (33.50mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can	Category	Capacitors
SeriesUBTCapacitance150μFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency651mA @ 100kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.319° (33.50mm)Surface Mount Land Size-Package / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance150µFTolerance±20%Voltage - Rated60VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency434mA @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseKatial, Can	Package	Radial, Can
Tolerance±0%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency434mA @ 120HzBipple Current - High Frequency651mA @ 100kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Hight - Seated (Max)1.319° (33.50mm)Surface Mount Land Size-Package / CaseRatial, Can	Series	UBT
Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency434mA @ 120HzBinpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	150µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency434mA @ 120HzBipple Current - High Frequency651mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Pounting TypeRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency434mA @ 120HzBipple Current - High Frequency651mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can	Voltage - Rated	160V
Operating Temperature-40°C ~ 125°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency434mA @ 120HzBripple Current - High Frequency651mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Package / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency434mA @ 120HzRipple Current - High Frequency651mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 125°C
ApplicationsAutomotiveRipple Current - Low Frequency434mA @ 120HzRipple Current - High Frequency651mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 125°C
InAdditionRipple Current - Low Frequency434mA @ 120HzRipple Current - High Frequency651mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency651mA @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	Automotive
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	434mA @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	651mA @ 100kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.319" (33.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.319" (33.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

#### **UBT2C151MHD** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **UBT2C151MHD Payment Methods**



# **UBT2C151MHD Shipping Methods**



If you have any question about UBT2C151MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com