



UBX1E471MHL Information



For Reference Only

Part Number UBX1E471MHL

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 470UF 20% 25V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UBX1E471MHL Specifications

Category Capacitors Package Radial, Can Series UBX Capacitance 470µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 150°C Operating Temperature -55°C ~ 150°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 400mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can UBX Capacitance UBX Capacitance 470µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 150°C Operating Temperature -55°C ~ 150°C Polarization Polar Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - Low Frequency Ripple Curre	Manufacturer Part Number	UBX1E471MHL
Package Radial, Can Series UBX Capacitance 470μF Tolerance ±20% Voltage - Rated 25 V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 150°C Operating Temperature -55°C ~ 150°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 400mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Nichicon
Package Radial, Can Series UBX Capacitance 470μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 150°C Operating Temperature -55°C ~ 150°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 400mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series UBX Capacitance 470μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 150°C Operating Temperature -55°C ~ 150°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 400mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 470μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 150°C Operating Temperature -55°C ~ 150°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 400mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 150°C Operating Temperature -55°C ~ 150°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 400mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UBX
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 150°C Operating Temperature -55°C ~ 150°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency Boom A @ 120Hz Rippedance - Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Capacitance	470μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 150°C Operating Temperature -55°C ~ 150°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 800mA @ 120Hz Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 150°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - High Frequency Ripple Current - Operating Temperature - Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 150°C -55°C ~ 150°C -000 Automotive 400mA @ 120Hz 800mA @ 100kHz -0.295" (7.50mm) 0.630" Dia (16.00mm) 1.043" (26.50mm) Through Hole Radial, Can	Voltage - Rated	25V
Operating Temperature -55°C ~ 150°C Polarization Polar Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Room A @ 120Hz Room A @ 100kHz - Lead Spacing Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency RoomA @ 120Hz RoomA @ 100kHz RoomA @ 100	Lifetime @ Temp.	2000 Hrs @ 150°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency RoomA @ 100kHz	Operating Temperature	-55°C ~ 150°C
Ripple Current - Low Frequency Ripple Current - High Frequency 800mA @ 100kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Applications	Automotive
Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	400mA @ 120Hz
Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	800mA @ 100kHz
Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 1.043" (26.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	1.043" (26.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report error

UBX1E471MHL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UBX1E471MHL Payment Methods



















UBX1E471MHL Shipping Methods













If you have any question about UBX1E471MHL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com