

UBX1J101MPL

UBX1J101MPL Information

www.caer.com	Part Number	UBX1J101MPL	
	Manufacturer	Nichicon	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 100UF 20% 63V RADIAL	
	Package	Radial, Can	
		For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UBX1J101MPL Specifications

ManufacturerNichiconCapacitorsCapacitorsAtuminum Electrolytic CapacitorsPackageRadial, CanSeriesUBXCapacitance100µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 150°COperating Temperature55°C ~ 150°CPolarizationAutomotiveApplicationsSt5mA @ 120HzRipple Current - High Frequency-Inpedance-Lied Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseKaila, Can	_	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUBXCapacitance100µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Impedance-Lifetime Spacing0.197" (5.00mm)Siz / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can	Manufacturer Part Number	UBX1J101MPL
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUBXCapacitance100µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 150°COperating Temperature55°C ~ 150°CPolarization75°C ~ 150°CApplications355mA @ 120HzRipple Current - Low Frequency555°MA @ 120HzRipple Current - High Frequency-Impedance-Lad Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUBXCapacitance100µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplications355mA @ 120HzRiple Current - High Frequency-Impedance-Lad Spacing0.197" (5.00mm)Size / Dimension0.344" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesUBXCapacitance100μFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency355mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance100µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseKaila, Can	Package	Radial, Can
Tolerance±0%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency355mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UBX
Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency355mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Pockage / CaseRatial, Can	Capacitance	100µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency355mA @ 120HzBipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeFnrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.1000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency355mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can	Voltage - Rated	63V
Operating Temperature -55°C ~ 150°C Polarization Polar Applications Automotive Apple Current - Low Frequency 355mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency355mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 150°C
ApplicationsAutomotiveRipple Current - Low Frequency355mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 150°C
InStand & Stand & 120HzRipple Current - Low Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency-Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	Automotive
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	355mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.846" (21.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UBX1J101MPL Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UBX1J101MPL Payment Methods



UBX1J101MPL Shipping Methods



If you have any question about UBX1J101MPL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com