



UBX1J680MPL Information



For Reference Only

Part Number UBX1J680MPL

Manufacturer Nichicon Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 68UF 20% 63V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UBX1J680MPL Specifications

Manufacturer Part Number UBX11680MPL Manufacturer Nichicon Category Capacitors Package Radial, Can Series UBX Capacitance 68μF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 150°C Operating Temperature -55°C ~ 150°C Polarization Automotive Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 560mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can Report errors?	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UBX Capacitance 68µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 150°C Operating Temperature -55°C ~ 150°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency S60mA @ 120Hz Ripple Current - High Frequency Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can	Manufacturer Part Number	UBX1J680MPL
PackageRadial, CanSeriesUBXCapacitance68μFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency280mA @ 120HzRipple Current - High Frequency560mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Nichicon
Package Radial, Can Series UBX Capacitance 68μF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 150°C Operating Temperature -55°C ~ 150°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 560mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series UBX Capacitance 68µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 150°C Operating Temperature -55°C ~ 150°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 560mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance68μFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifettime @ Temp.1000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency280mA @ 120HzRipple Current - High Frequency560mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 150°C Operating Temperature -55°C ~ 150°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 560mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UBX
Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency280mA @ 120HzRipple Current - High Frequency560mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	68μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -55°C ~ 150°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Ead Spacing Outer of Dimension Lead Spacing Outer of Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Fackage / Case - Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 150°C Polarization Polar Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency 560mA @ 120Hz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case 1000 Hrs @ 150°C Automotive -55°C ~ 150°C Automotive 280mA @ 120Hz 560mA @ 120Hz 1000 Hrs @ 120Hz 1000 Hrs @ 150°C 1000 Hrs @ 150°C	Voltage - Rated	63V
Operating Temperature Polarization Polar Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Selections Automotive Ripple Current - High Frequency Selections Ripple Current - High Frequency Selections Selections Size / Dimension Size / Dimension Dimension Oight - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications Automotive Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 560mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	1000 Hrs @ 150°C
Applications Ripple Current - Low Frequency 280mA @ 120Hz Ripple Current - High Frequency 560mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 150°C
Ripple Current - Low Frequency Ripple Current - High Frequency 560mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	Automotive
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	280mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.689" (17.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	560mA @ 100kHz
Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.689" (17.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.689" (17.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UBX1J680MPL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UBX1J680MPL Payment Methods



















UBX1J680MPL Shipping Methods













If you have any question about UBX1J680MPL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com