

UBX1K221MHL

UBX1K221MHL Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UBX1K221MHL Specifications

ManufacturerNichiconCagacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUBXCapacitance20µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationAutomotiveRipple Current - Low Frequency625mA @ 120HzRipple Current - High Frequency1.25A @ 100kHzImpedance-Lied Spacing0.295° (7.50mm)Size / Dimension1.043° (26.50mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUBXCapacitance20µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency625mA @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer Part Number	UBX1K221MHL
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUBXCapacitance220µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 150°COperating Temperature55°C ~ 150°CPolarizationAutomotiveRipple Current - Low Frequency625mA @ 120HzRipple Current - High Frequency1.25A @ 100kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUBXCapacitance220µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency625mA @ 120HzRipple Current - High Frequency0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesUBXCapacitance220µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency625mA @ 120HzInpedance-Lead Spacing0.295° (7.50mn)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance220µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency625mA @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)-Surface Mount Land Size-Polaring TypeThrough HolePackage / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency625mA @ 120HzRipple Current - High Frequency.255°C 7.50°MImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.043° (26.50mm)Surface Mount Land Size-Pokage / CaseReidia, Can	Series	UBX
Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency625mA @ 120HzBipple Current - High Frequency1.25A @ 100kHzImpedance-Lead Spacing0.630° Dia (16.00mm)Size / Dimension1.043° (26.50mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseRatial, Can	Capacitance	220µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency625mA @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Pounting TypeRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 150°COperating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency625mA @ 120HzRipple Current - High Frequency1.25A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can	Voltage - Rated	80V
Operating Temperature-55°C ~ 150°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency625mA @ 120HzRipple Current - High Frequency1.25A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency625mA @ 120HzRipple Current - High Frequency1.25A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 150°C
ApplicationsAutomotiveRipple Current - Low Frequency625mA @ 120HzRipple Current - High Frequency1.25A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 150°C
InInRipple Current - Low Frequency625mA @ 120HzRipple Current - High Frequency1.25A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
Ripple Current - High Frequency1.25A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	Automotive
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	625mA @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.25A @ 100kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.043" (26.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UBX1K221MHL Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UBX1K221MHL Payment Methods



UBX1K221MHL Shipping Methods



If you have any question about UBX1K221MHL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com