

### **UC2714NG4 Information**



For Reference Only

Part Number UC2714NG4

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

**Description** IC COMPLEMENT SW FET DRVR 8-DIP

**Package** 8-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **UC2714NG4 Specifications**

Manufacturer Part Number         UC2714NG4           Manufacturer         Texas Instruments           Category         Integrated Circuits (ICs)           Package         8-DIP (0.300", 7.62mm)           Series         -           Driven Configuration         Low-Side           Channel Type         Synchronous           Number of Drivers         2           Gate Type         N-Channel, P-Channel MOSFET           Voltage - Supply         7 V ~ 20 V           Logic Voltage - VIL, VIH         0.8V, 2V           Current - Peak Output (Source, Sink)         500mA, 1A           Input Type         Non-Inverting           High Side Voltage - Max (Bootstrap)         -           Rise / Fall Time (Typ)         30ns, 25ns           Operating Temperature         -40°C ~ 150°C (TJ)           Mounting Type         Through Hole           Package / Case         8-DIP (0.300", 7.62mm)           Supplier Device Package         8-PDIP		
Category  Package  Package  8-DIP (0.300", 7.62mm)  Series  - Driven Configuration  Channel Type  Synchronous  Number of Drivers  2  Gate Type  N-Channel, P-Channel MOSFET  Voltage - Supply  T V ~ 20 V  Logic Voltage - VIL, VIH  0.8V, 2V  Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Fise / Fall Time (Typ)  Operating Temperature  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package  8-PDIP	Manufacturer Part Number	UC2714NG4
Package 8-DIP (0.300", 7.62mm)  Series - Driven Configuration Low-Side  Channel Type Synchronous  Number of Drivers 2  Gate Type N-Channel, P-Channel MOSFET  Voltage - Supply 7 V ~ 20 V  Logic Voltage - VIL, VIH 0.8V, 2V  Current - Peak Output (Source, Sink) 500mA, 1A  Input Type Non-Inverting  High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 30ns, 25ns  Operating Temperature -40°C ~ 150°C (TJ)  Mounting Type Through Hole  Package / Case 8-DIP (0.300", 7.62mm)  Supplier Device Package	Manufacturer	Texas Instruments
Package8-DIP (0.300", 7.62mm)Series-Driven ConfigurationLow-SideChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply7 V ~ 20 VLogic Voltage - VIL, VIH0.8V, 2VCurrent - Peak Output (Source, Sink)500mA, 1AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)30ns, 25nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-PDIP	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationLow-SideChannel TypeSynchronousNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply7 V ~ 20 VLogic Voltage - VIL, VIH0.8V, 2VCurrent - Peak Output (Source, Sink)500mA, 1AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)30ns, 25nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-PDIP		PMIC - Gate Drivers
Driven Configuration  Low-Side  Channel Type  Synchronous  Number of Drivers  2  Gate Type  N-Channel, P-Channel MOSFET  Voltage - Supply  Logic Voltage - VIL, VIH  0.8V, 2V  Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Package	8-DIP (0.300", 7.62mm)
Channel Type  Number of Drivers  2  Gate Type  N-Channel, P-Channel MOSFET  Voltage - Supply  7 V ~ 20 V  Logic Voltage - VIL, VIH  0.8V, 2V  Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  30ns, 25ns  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Series	-
Number of Drivers  Gate Type  N-Channel, P-Channel MOSFET  Voltage - Supply  To V ~ 20 V  Logic Voltage - VIL, VIH  0.8V, 2V  Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Driven Configuration	Low-Side
Gate Type  N-Channel, P-Channel MOSFET  Voltage - Supply  To V ~ 20 V  Logic Voltage - VIL, VIH  0.8V, 2V  Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)	Channel Type	Synchronous
Voltage - Supply  Logic Voltage - VIL, VIH  0.8V, 2V  Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH0.8V, 2VCurrent - Peak Output (Source, Sink)500mA, 1AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)30ns, 25nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-PDIP	Gate Type	N-Channel, P-Channel MOSFET
Current - Peak Output (Source, Sink)  Input Type  Non-Inverting  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Voltage - Supply	7 V ~ 20 V
Input Type  High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Logic Voltage - VIL, VIH	0.8V, 2V
High Side Voltage - Max (Bootstrap)  Rise / Fall Time (Typ)  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Current - Peak Output (Source, Sink)	500mA, 1A
Rise / Fall Time (Typ)  30ns, 25ns  Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package	Input Type	Non-Inverting
Operating Temperature  -40°C ~ 150°C (TJ)  Mounting Type  Through Hole  Package / Case  8-DIP (0.300", 7.62mm)  Supplier Device Package  8-PDIP	High Side Voltage - Max (Bootstrap)	-
Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Rise / Fall Time (Typ)	30ns, 25ns
Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Operating Temperature	-40°C ~ 150°C (TJ)
Supplier Device Package 8-PDIP	Mounting Type	Through Hole
	Package / Case	8-DIP (0.300", 7.62mm)
Report errors?	Supplier Device Package	8-PDIP
		Report errors?

#### **UC2714NG4 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **UC2714NG4 Payment Methods**



















### **UC2714NG4 Shipping Methods**













If you have any question about UC2714NG4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com