

UCA2D680MHD

UCA2D680MHD Information

www.elsentr.com	Part Number Manufacturer Category Description Package	Capacitors Aluminum Electrolytic Capacitors CAP ALUM 68UF 20% 200V RADIAL Radial, Can	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UCA2D680MHD Specifications

Manufacturer Part NumberUCA2D680MHDManufacturerNichiconCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUCACapacitance68µFTolerance200%Voltage - Rated200VESR (Equivalent Series Resistance)-Operating Temperature2000 Hrs @ 105°COperating Temperature2000 Hrs @ 105°CApplicationsGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency350mA @ 100kHzImpedance-Lead Spacing0.197" (S.00mm)Size / Dimension0.492"Dia (12.50mm)Mirght - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Name Manuel M	
CategoryCapacitorsPackageRadial, CanPackageRadial, CanSeriesUCACapacitance68µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature25°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency475mA @ 120HzInpedance-Liad Spacing0.197" (5.00mm)Size / Dimension1.043" (26.50mm)Hight - Seated (Max)-Mounting TypeThrough Hole	
Auminum Electrolytic CapacitorsPackageRadial, CanSeriesUCACapacitance68µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency475mA @ 120HzNipedance-Licad Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)-Mounting TypeThrough Hole	
PackageRadial, CanSeriesUCACapacitance68µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency950mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	
SeriesUCASeriesUCACapacitance68µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency475mA @ 120HzInpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Mounting TypeThrough Hole	
Capacitance68μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency475mA @ 120HzInpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Mounting TypeThrough Hole	
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency475mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	
Voltage - Rated200VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency475mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension1.043" (26.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	
ESR (Equivalent Series Resistance)-ESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency475mA @ 120HzRipple Current - High Frequency950mA @ 100kHzImpedance-Size / Dimension0.197" (5.00mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	
Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency475mA @ 120HzRipple Current - High Frequency950mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	
Operating Temperature-25°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency475mA @ 120HzRipple Current - High Frequency950mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency475mA @ 120HzRipple Current - High Frequency950mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	
ApplicationsGeneral PurposeRipple Current - Low Frequency475mA @ 120HzRipple Current - High Frequency950mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	
Ripple Current - Low Frequency475mA @ 120HzRipple Current - High Frequency950mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	
Ripple Current - High Frequency950mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	
Height - Seated (Max)1.043" (26.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	
Surface Mount Land Size - Mounting Type Through Hole	
Mounting Type Through Hole	
Package / Case Radial, Can	
	Report errors?

UCA2D680MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UCA2D680MHD Payment Methods



UCA2D680MHD Shipping Methods



If you have any question about UCA2D680MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com