



UCC27322DR Information



For Reference Only

Part Number UCC27322DR

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

Description IC MOSFET DRIVER SGL HS 9A 8SOIC

Package 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UCC27322DR Specifications

Manufacturer Part Number UCC27322DR Manufacturer Texas Instruments Category Integrated Circuits (ICs) PMIC - Gate Drivers Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Low-Side Channel Type Single Number of Drivers 1 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4 V ~ 15 V Logic Voltage - VIL, VIH 1.1V, 2.7V Current - Peak Output (Source, Sink) 9A, 9A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 20ns, 20ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC		
Category Package Package Resolt (0.154", 3.90mm Width) Series - Driven Configuration Channel Type Single Number of Drivers 1 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4 V ~ 15 V Logic Voltage - VIL, VIH 1.1V, 2.7V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Fise / Fall Time (Typ) Operating Temperature Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Manufacturer Part Number	UCC27322DR
Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Low-Side Channel Type Single Number of Drivers 1 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4 V ~ 15 V Logic Voltage - VIL, VIH 1.1V, 2.7V Current - Peak Output (Source, Sink) 9A, 9A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 20ns, 20ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Manufacturer	Texas Instruments
Package8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationLow-SideChannel TypeSingleNumber of Drivers1Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4 V ~ 15 VLogic Voltage - VIL, VIH1.1V, 2.7VCurrent - Peak Output (Source, Sink)9A, 9AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)20ns, 20nsOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationLow-SideChannel TypeSingleNumber of Drivers1Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4 V ~ 15 VLogic Voltage - VIL, VIH1.1V, 2.7VCurrent - Peak Output (Source, Sink)9A, 9AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)20ns, 20nsOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC		PMIC - Gate Drivers
Driven Configuration Channel Type Single Number of Drivers 1 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply Logic Voltage - VIL, VIH Logic Voltage - VIL, VIH Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Package	8-SOIC (0.154", 3.90mm Width)
Channel Type Number of Drivers 1 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4 V ~ 15 V Logic Voltage - VIL, VIH Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Series	-
Number of Drivers Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4 V ~ 15 V Logic Voltage - VIL, VIH 1.1V, 2.7V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Driven Configuration	Low-Side
Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4 V ~ 15 V Logic Voltage - VIL, VIH 1.1V, 2.7V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Channel Type	Single
Voltage - Supply Logic Voltage - VIL, VIH 1.1V, 2.7V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Number of Drivers	1
Logic Voltage - VIL, VIH Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Gate Type	N-Channel, P-Channel MOSFET
Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Voltage - Supply	4 V ~ 15 V
Input Type High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Logic Voltage - VIL, VIH	1.1V, 2.7V
High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Current - Peak Output (Source, Sink)	9A, 9A
Rise / Fall Time (Typ) 20ns, 20ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Input Type	Non-Inverting
Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	High Side Voltage - Max (Bootstrap)	-
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Rise / Fall Time (Typ)	20ns, 20ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Operating Temperature	-55°C ~ 150°C (TJ)
Supplier Device Package 8-SOIC	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	8-SOIC
		Report errors?

UCC27322DR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UCC27322DR Payment Methods





















UCC27322DR Shipping Methods













If you have any question about UCC27322DR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com