

UCC27424DG4 Information



For Reference Only

Part Number UCC27424DG4

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

Description IC MOSFET DRIVR DUAL HS 4A 8SOIC

Package 8-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UCC27424DG4 Specifications

Manufacturer Part Number UCC27424DG4 Manufacturer Texas Instruments Category Integrated Circuits (ICs) PMIC - Gate Drivers Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Low-Side Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) 4A, 4A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 20ns, 15ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC		
Category Package Package Resolt (0.154", 3.90mm Width) Series Low-Side Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply Logic Voltage - VIL, VIH Logic Voltage - VIL, VIH Lurent - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Fise / Fall Time (Typ) Operating Temperature Package / Case S-SOIC (0.154", 3.90mm Width) Supplier Device Package R-SOIC (0.154", 3.90mm Width)	Manufacturer Part Number	UCC27424DG4
Package 8-SOIC (0.154", 3.90mm Width) Series - Driven Configuration Low-Side Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) 4A, 4A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 20ns, 15ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Manufacturer	Texas Instruments
Package8-SOIC (0.154", 3.90mm Width)Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4 V ~ 15 VLogic Voltage - VIL, VIH1V, 2VCurrent - Peak Output (Source, Sink)4A, 4AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)20ns, 15nsOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4 V ~ 15 VLogic Voltage - VIL, VIH1V, 2VCurrent - Peak Output (Source, Sink)4A, 4AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)20ns, 15nsOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC		PMIC - Gate Drivers
Driven Configuration Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply Logic Voltage - VIL, VIH Logic Voltage - VIL, VIH Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Package	8-SOIC (0.154", 3.90mm Width)
Channel Type Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Series	-
Number of Drivers Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Driven Configuration	Low-Side
Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Channel Type	Independent
Voltage - Supply Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Gate Type	N-Channel, P-Channel MOSFET
Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Voltage - Supply	4 V ~ 15 V
Input Type High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Logic Voltage - VIL, VIH	1V, 2V
High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package	Current - Peak Output (Source, Sink)	4A, 4A
Rise / Fall Time (Typ) 20ns, 15ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Input Type	Non-Inverting
Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	High Side Voltage - Max (Bootstrap)	-
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Rise / Fall Time (Typ)	20ns, 15ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Supplier Device Package 8-SOIC	Operating Temperature	-55°C ~ 150°C (TJ)
Supplier Device Package 8-SOIC	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	8-SOIC
		Report errors?

UCC27424DG4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UCC27424DG4 Payment Methods



















UCC27424DG4 Shipping Methods













If you have any question about UCC27424DG4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com