

UCC37323P Information



For Reference Only

Part Number UCC37323P

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

Description IC DUAL HS PWR FET DRVR 8-DIP

Package 8-DIP (0.300", 7.62mm)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UCC37323P Specifications

Manufacturer Part Number UCC37323P Manufacturer Texas Instruments Category Integrated Circuits (ICs) Package 8-DIP (0.300", 7.62mm) Series - Driven Configuration Low-Side Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) 4A, 4A Input Type Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 20ns, 15ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP		
Category Integrated Circuits (ICs) PMIC - Gate Drivers Package 8-DIP (0.300", 7.62mm) Series - Driven Configuration Low-Side Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature Operating Temperature August A	Manufacturer Part Number	UCC37323P
Package 8-DIP (0.300", 7.62mm) Series - Driven Configuration Low-Side Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) 4A, 4A Input Type Inverting High Side Voltage - Max (Bootstrap) - Rise / Fall Time (Typ) 20ns, 15ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Manufacturer	Texas Instruments
Package8-DIP (0.300", 7.62mm)Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 15 VLogic Voltage - VIL, VIH1V, 2VCurrent - Peak Output (Source, Sink)4A, 4AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)20ns, 15nsOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-PDIP	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationLow-SideChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel, P-Channel MOSFETVoltage - Supply4.5 V ~ 15 VLogic Voltage - VIL, VIH1V, 2VCurrent - Peak Output (Source, Sink)4A, 4AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)20ns, 15nsOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-PDIP		PMIC - Gate Drivers
Driven Configuration Channel Type Independent Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply Logic Voltage - VIL, VIH Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Package	8-DIP (0.300", 7.62mm)
Channel Type Number of Drivers 2 Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 20ns, 15ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Series	-
Number of Drivers Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature Operating Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Driven Configuration	Low-Side
Gate Type N-Channel, P-Channel MOSFET Voltage - Supply 4.5 V ~ 15 V Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature Operating Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Channel Type	Independent
Voltage - Supply Logic Voltage - VIL, VIH 1V, 2V Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH1V, 2VCurrent - Peak Output (Source, Sink)4A, 4AInput TypeInvertingHigh Side Voltage - Max (Bootstrap)-Rise / Fall Time (Typ)20ns, 15nsOperating Temperature-55°C ~ 150°C (TJ)Mounting TypeThrough HolePackage / Case8-DIP (0.300", 7.62mm)Supplier Device Package8-PDIP	Gate Type	N-Channel, P-Channel MOSFET
Current - Peak Output (Source, Sink) Input Type Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Voltage - Supply	4.5 V ~ 15 V
Input Type High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Logic Voltage - VIL, VIH	1V, 2V
High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 20ns, 15ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Current - Peak Output (Source, Sink)	4A, 4A
Rise / Fall Time (Typ) 20ns, 15ns Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package	Input Type	Inverting
Operating Temperature -55°C ~ 150°C (TJ) Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	High Side Voltage - Max (Bootstrap)	-
Mounting Type Through Hole Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Rise / Fall Time (Typ)	20ns, 15ns
Package / Case 8-DIP (0.300", 7.62mm) Supplier Device Package 8-PDIP	Operating Temperature	-55°C ~ 150°C (TJ)
Supplier Device Package 8-PDIP	Mounting Type	Through Hole
	Package / Case	8-DIP (0.300", 7.62mm)
Report errors?	Supplier Device Package	8-PDIP
		Report errors?

UCC37323P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UCC37323P Payment Methods


































If you have any question about UCC37323P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com