

UCY2C331MHD

UCY2C331MHD Information

www.troisener.com	Part Number Manufacturer Category Description Package	Capacitors Aluminum Electrolytic Capacitors CAP ALUM 330UF 20% 160V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UCY2C331MHD Specifications

CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUCYCapacitance30µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - High Frequency3.02A @ 100kHzImpedance-Lead Spacing0.295°(7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.299°(33.00mm)Surface Mount Land Size-Pokage / CaseMail, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUCYCapacitance30µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - High Frequency3.02A @ 100kHzImpedance-Lead Spacing0.295°(7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.299°(33.00mm)Surface Mount Land Size-Pokage / CaseMail, Can	Manufacturer Part Number	UCY2C331MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUCYCapacitance330µFTolerance±20%Voltage - Rated60VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplications5.11 A @ 120HzRipple Current - Low Frequency3.02A @ 100kHzImpedance-Lead Spacing0.295°(7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.299° (33.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUCYCapacitance330µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency3.02A @ 100kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.630° Dia (16.00mm)Height - Seated (Max)1.299° (33.00mm)Surface Mount Land Size-Pokage / CaseKadial, Can	Category	Capacitors
SeriesUCYCapacitance330µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.02A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.519" (3.00mm)Height - Seated (Max)1.299" (33.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can		Aluminum Electrolytic Capacitors
Capacitance330µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 120HzInpedance-Lead Spacing0.295° (7.50mn)Size / Dimension1.299° (3.00mm)Height - Seated (Max)1.299° (3.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 120HzImpedance-Lead Spacing0.630° Dia (16.00mm)Size / Dimension1.299° (33.00mm)Height - Seated (Max)1.299° (33.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UCY
Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.02A @ 100kHzImpedance-Lead Spacing0.295°(7.50mm)Size / Dimension1.299°(33.00mm)Height - Seated (Max)1.299°(33.00mm)Surface Mount Land Size-Pockage / CaseRatial, Can	Capacitance	330µF
LocESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 120HzMippedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.299" (33.00mm)Height - Seated (Max)1.299" (33.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 120HzRipple Current - High Frequency3.02A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.299" (33.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	Voltage - Rated	160V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 120HzBipple Current - High Frequency3.02A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.299" (33.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 120HzRipple Current - High Frequency3.02A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.299" (33.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	12000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 120HzRipple Current - High Frequency3.02A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.299" (33.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Ripple Current - Low Frequency1.51A @ 120HzRipple Current - High Frequency3.02A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.299" (33.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency3.02A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.299" (33.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.299" (33.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	1.51A @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.299" (33.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	3.02A @ 100kHz
Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)1.299" (33.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.299" (33.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.299" (33.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UCY2C331MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UCY2C331MHD Payment Methods



UCY2C331MHD Shipping Methods



If you have any question about UCY2C331MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com