



UCY2G120MPD Information



For Reference Only

Part Number UCY2G120MPD

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 12UF 20% 400V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UCY2G120MPD Specifications

Manufacturer Part Number UCY2G120MPD Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UCY Capacitance 12μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 175mA @ 120Hz Ripple Current - High Frequency 350mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	_	
Category Capacitors Package Radial, Can Series UCY Capacitance 12µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 175mA @ 120Hz Ripple Current - High Frequency 350mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	UCY2G120MPD
Package Radial, Can Series UCY Capacitance 12μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 175mA @ 120Hz Ripple Current - High Frequency 350mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Nichicon
Package Radial, Can Series UCY Capacitance 12μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 175mA @ 120Hz Ripple Current - High Frequency 350mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series UCY Capacitance 12μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 175mA @ 120Hz Ripple Current - High Frequency 350mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 12µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 175mA @ 120Hz Ripple Current - High Frequency 350mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 175mA @ 120Hz Ripple Current - High Frequency 350mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UCY
Voltage - Rated400 VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency175mA @ 120HzRipple Current - High Frequency350mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	12μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 12000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 175mA @ 120Hz Ripple Current - High Frequency 350mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 350mA @ 120Hz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 12000 Hrs @ 105°C -40°C ~ 105°C -40°C -40°C ~ 105°C -40°C -40	Voltage - Rated	400V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 350mA @ 120Hz Rippedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 175mA @ 120Hz Ripple Current - High Frequency 350mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	12000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 175mA @ 120Hz Ripple Current - High Frequency 350mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency S50mA @ 100kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	175mA @ 120Hz
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - High Frequency	350mA @ 100kHz
Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.846" (21.50mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.846" (21.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
D	Package / Case	Radial, Can
Report errors?		Report errors?

UCY2G120MPD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UCY2G120MPD Payment Methods



















UCY2G120MPD Shipping Methods













If you have any question about UCY2G120MPD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com