

UCY2V330MHD

UCY2V330MHD Information

wy. neise er.com	Part Number Manufacturer Category Description Package	UCY2V330MHD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 33UF 20% 350V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UCY2V330MHD Specifications

Package / Case Radial, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUCYCapacitance3J#FTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime Temp.12000 Hrs @ 105°COperating Temperature90arApplicationsGeneral PurposeRipple Current - High Frequency380m A @ 120HzNipple Current - High Frequency360m A @ 100kHzImpedance-Lied Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeHrouge HolePackage / CaseKadia, Can	Manufacturer Part Number	UCY2V330MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUCYCapacitance33µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency380mA @ 120HzRipple Current - High Frequency760mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.440°C (1.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Package / CaseKadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUCYCapacitance33µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency380mA @ 120HzImpedance-Lided Spacing0.197" (5.00mm)Siz / Dimension0.492" Dia (12.50mm)Siz / Dimension0.446" (11.50mm)Siraface Mount Land Size-Mounting TypeHolePackage / CaseKalial, Can	Category	Capacitors
SeriesUCYCapacitance33μFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency380mA @ 120HzInpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaid, Can		Aluminum Electrolytic Capacitors
Capacitance33µFTolerance±20%Voltage - Rated550VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency380mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency380mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Series	UCY
Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency380mA @ 120HzMippedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Capacitance	33µF
LocESR (Equivalent Series Resistance)-Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency380mA @ 120HzMippedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.12000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency380mA @ 120HzRipple Current - High Frequency760mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeFackage / CaseRackage / CaseRadial, Can	Voltage - Rated	350V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency380mA @ 120HzBipple Current - High Frequency760mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency380mA @ 120HzRipple Current - High Frequency760mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	12000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency380mA @ 120HzRipple Current - High Frequency760mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 105°C
AARipple Current - Low Frequency380mA @ 120HzRipple Current - High Frequency760mA @ 100kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the first	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	380mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	760mA @ 100kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.846" (21.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.846" (21.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UCY2V330MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UCY2V330MHD Payment Methods



UCY2V330MHD Shipping Methods



If you have any question about UCY2V330MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com