

### **UD2-3NE Information**

ww.helsener.com

Part Number UD2-3NE
Manufacturer KEMET
Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE DPDT 1A 3V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **UD2-3NE Specifications**

Manufacturer Part Number  Manufacturer  KEMET  Relays  Signal Relays, Up to 2 Amps  Package  - Series  UD2  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  33.3mA  Coil Voltage  3VDC  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  1A  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  Ims  Features  -  Mounting Type  Surface Mount  Termination Style  KEMET  KEMET  KEMET  AUDC  Amps  Signal Relays, Up to 2 Amps  Signal Relays  LOD  Amps  Signal Relays  LOD  Amps  Seport errors?		
CategoryRelaysPackage-SeriesUD2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.4 VDCTurn Off Voltage (Min)0.3 VDCOperate Time2msRelease Time1msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	UD2-3NE
Package - Series UD2 Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style General Purpose Annual Canada Suppose Surface Mount Termination Style General Purpose General Purpose (ID2) UD2 Seneral Purpose (ID2) UD2 Seneral Purpose (ID2) Surface Mount Turn Off Voltage (ID2) Surface Mount Termination Style Gull Wing	Manufacturer	KEMET
Package - UD2 Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style General Purpose 1 Coneral Purpose 1 Cone	Category	Relays
SeriesUD2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.4 VDCTurn Off Voltage (Min)0.3 VDCOperate Time2msRelease TimeImsFeatures-Mounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.4 VDCTurn Off Voltage (Min)0.3 VDCOperate Time2msRelease TimeImsFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil TypeNon LatchingCoil Current33.3mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.4 VDCTurn Off Voltage (Min)0.3 VDCOperate Time2msRelease TimeImsFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Series	UD2
Coil Current 33.3mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	General Purpose
Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.4 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 2ms Release Time 1ms Features Mounting Type Surface Mount Termination Style Gull Wing	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  2.4 VDC  Turn Off Voltage (Min)  0.3 VDC  Operate Time  Release Time  Ims  Features  -  Mounting Type  Surface Mount  Termination Style  DPDT (2 Form C)  1A  250VAC, 220VDC - Max  2.4 VDC  1.5 VDC  1.5 VDC  2.6 VDC  2.7 VDC  2.7 VDC  3.8 VDC  4.8 VDC  5.8 VDC  5.8 VDC  6.9 VDC	Coil Current	33.3mA
Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  2.4 VDC  Turn Off Voltage (Min)  0.3 VDC  Operate Time  2ms  Release Time  1ms  Features  -  Mounting Type  Surface Mount  Termination Style	Coil Voltage	3VDC
Switching Voltage 250VAC, 220VDC - Max  Turn On Voltage (Max) 2.4 VDC  Turn Off Voltage (Min) 0.3 VDC  Operate Time 2ms  Release Time 1ms  Features  Mounting Type Surface Mount  Termination Style Gull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  Ims  Features  Mounting Type  Surface Mount  Termination Style  2.4 VDC  0.3 VDC  2ms	Contact Rating (Current)	1A
Turn Off Voltage (Min)  Operate Time  2ms  Release Time  1ms  Features  -  Mounting Type  Surface Mount  Termination Style  Gull Wing	Switching Voltage	250VAC, 220VDC - Max
Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn On Voltage (Max)	2.4 VDC
Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	0.3 VDC
Features - Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	2ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	1ms
Termination Style Gull Wing	Features	-
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
		Report errors?

### **UD2-3NE Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **UD2-3NE Payment Methods**





















### **UD2-3NE Shipping Methods**













If you have any question about UD2-3NE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com