

UD2-3NUN-L Information

Part Number UD2-3NUN-L

Manufacturer KEMET Category Relays

Signal Relays, Up to 2 Amps

RELAY GEN PURPOSE DPDT 1A 3V **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com





Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UD2-3NUN-L Specifications

Manufacturer Part Number UD2-3NUN-L Manufacturer KEMET Category Relays Signal Relays, Up to 2 Amps Package - Series UD2 Relay Type General Purpose Coil Type Non Latching Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 2ms Release Time Ims Features - Mounting Type Surface Mount Termination Style Gull Wing		
CategoryRelaysPackage-SeriesUD2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time2msRelease Time1 msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	UD2-3NUN-L
Package-SeriesUD2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time2msRelease Time1 msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer	KEMET
Package-SeriesUD2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time2msRelease Time1msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Category	Relays
SeriesUD2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time2msRelease Time1 msFeatures-Mounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time2msRelease Time1 msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil TypeNon LatchingCoil Current46.7mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.25 VDCTurn Off Voltage (Min)0.3 VDCOperate Time2msRelease Time1msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Series	UD2
Coil Current 46.7mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	General Purpose
Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style DPDT (2 Form C) 1A 1A 250VAC, 220VDC - Max 2.25 VDC 1.3 VDC 2.3 VDC 2.3 VDC 2.3 VDC 2.3 VDC 3.3 VDC 4.3 VDC 5.4 VDC 5.5 VDC 6.7 VDC 6.8 VDC 6.9	Coil Current	46.7mA
Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Coil Voltage	3VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 2.25 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Contact Rating (Current)	1A
Turn Off Voltage (Min) Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Switching Voltage	250VAC, 220VDC - Max
Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn On Voltage (Max)	2.25 VDC
Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	0.3 VDC
Features - Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	2ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	1ms
Termination Style Gull Wing	Features	-
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
		Report errors?

UD2-3NUN-L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UD2-3NUN-L Payment Methods



















UD2-3NUN-L Shipping Methods













If you have any question about UD2-3NUN-L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com