

UD2-5NE-L Information

www.heisener.com

Part Number UD2-5NE-L
Manufacturer KEMET
Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE DPDT 1A 5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UD2-5NE-L Specifications

| Manufacturer Part Number UD2-5NE-L Manufacturer KEMET Category Relays Signal Relays, Up to 2 Amps Package - Series UD2 Relay Type General Purpose Coil Type Non Latching Coil Current 20mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 2ms Release Time Ims Features - Mounting Type Surface Mount Termination Style Gull Wing | | |
|--|--------------------------|-----------------------------|
| CategoryRelaysPackage-SeriesUD2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.5 VDCOperate Time2msRelease Time1 msFeatures-Mounting TypeSurface MountTermination StyleGull Wing | Manufacturer Part Number | UD2-5NE-L |
| Package-SeriesUD2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.5 VDCOperate Time2msRelease TimeImsFeatures-Mounting TypeSurface MountTermination StyleGull Wing | Manufacturer | KEMET |
| Package - UD2 Relay Type General Purpose Coil Type Non Latching Coil Current 20mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style General Purpose General Purpose 102 Seneral Purpose 102 Sun Latching 103 104 105 107 107 108 108 108 108 108 108 108 108 108 108 | Category | Relays |
| SeriesUD2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.5 VDCOperate Time2msRelease Time1msFeatures-Mounting TypeSurface MountTermination StyleGull Wing | | Signal Relays, Up to 2 Amps |
| Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.5 VDCOperate Time2msRelease Time1 msFeatures-Mounting TypeSurface MountTermination StyleGull Wing | Package | - |
| Coil TypeNon LatchingCoil Current20mACoil Voltage5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)4 VDCTurn Off Voltage (Min)0.5 VDCOperate Time2msRelease Time1msFeatures-Mounting TypeSurface MountTermination StyleGull Wing | Series | UD2 |
| Coil Current 20mA Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 2ms Release Time 1ms Features Mounting Type Surface Mount Termination Style Gull Wing | Relay Type | General Purpose |
| Coil Voltage 5VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 2ms Release Time 1ms Features Mounting Type Surface Mount Termination Style Gull Wing | Coil Type | Non Latching |
| Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 2ms Release Time Ims Features - Mounting Type Surface Mount Termination Style DPDT (2 Form C) 1A 1A 250VAC, 220VDC - Max 4 VDC 1 VDC 1 VDC 2 VDC 2 VDC 2 VDC 4 VDC 5 VDC 6 V | Coil Current | 20mA |
| Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing | Coil Voltage | 5VDC |
| Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 4 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 2ms Release Time 1ms Features Mounting Type Surface Mount Termination Style Gull Wing | Contact Form | DPDT (2 Form C) |
| Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Ims Features Mounting Type Surface Mount Termination Style 4 VDC 0.5 VDC 2ms 2ms Rule 2ms Surface Mount Gull Wing | Contact Rating (Current) | 1A |
| Turn Off Voltage (Min) Operate Time Release Time Ims Features Mounting Type Surface Mount Termination Style O.5 VDC 2ms Lms Surface Mount Gull Wing | Switching Voltage | 250VAC, 220VDC - Max |
| Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing | Turn On Voltage (Max) | 4 VDC |
| Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing | Turn Off Voltage (Min) | 0.5 VDC |
| Features - Mounting Type Surface Mount Termination Style Gull Wing | Operate Time | 2ms |
| Mounting Type Surface Mount Termination Style Gull Wing | Release Time | 1ms |
| Termination Style Gull Wing | Features | - |
| | Mounting Type | Surface Mount |
| Report errors? | Termination Style | Gull Wing |
| | | Report errors? |

UD2-5NE-L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UD2-5NE-L Payment Methods




































If you have any question about UD2-5NE-L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com