

UEP1J330MPD

Request a Quote

UEP1J330MPD Information

	Part Number	UEP1J330MPD
www.yeisoper.com	Manufacturer	Nichicon
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 33UF 20% 63V RADIAL
	Package	Radial, Can
		For the pricing/inventory/lead time, please contact
		us
For Reference Only		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UEP1J330MPD Specifications

Manufacturer Part NumberUEP1330MPDManufacturer And SeriesCapacitorsCategoryCapacitorsPackageRadial, CanPackageRadial, CanSeriesUEPCapacitance33µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - High Frequency98mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension0.51" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePownerPartonePownerPartonePownerPartoneSurface Mount Land Size-PownerPartonePownerPar	-	
CategoryCapacitorsAluminur Electrolytic CapacitorsPackageRadial, CanSeriesUEPCapacitance33µFTolerance±20%Voltage - Rated63∨ESR (Equivalent Series Resistance)-Lifetime Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRippe Current - High Frequency96mA @ 100 HrzImpedance-Liad Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Hight - Seated (Max)5.51" (14.00mm)Surface Mount Land Size-Mounting TypeFinogatica MathematicaPackage / CaseMail, Can	Manufacturer Part Number	UEP1J330MPD
IdentifyAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUEPCapacitance33µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Derating Temper1000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationGeneral PurposeApplications98mA @ 120HzRipple Current - High Frequency96mA @ 100HzImpedance-Lad Spacing0.197°(5.00mm)Size / Dimension0.394°Dia (10.00mm)Size / Dimension0.51°(14.00mm)Hight - Seated (Max)-Mouting TypeFnough HolePackage / CaseMaia (Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUEPCapacitance33µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature55°C ~ 105°C ~ 105°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency98mA @ 120HzImpedance-Lided Spacing0.197" (5.00mm)Size / Dimension0.511" (14.00mm)Size / Dimension5.51" (14.00mm)Surface Mount Land Size-Mounting TypeMouting TypePackage / CaseKaid, Can	Category	Capacitors
SeriesUEPCapacitance33µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - High Frequency98mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Size / Dimension0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can		Aluminum Electrolytic Capacitors
Capacitance33µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - High Frequency98mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalia, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency98mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Hounting TypeFnough HolePackage / CaseRadial, Can	Series	UEP
Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency98mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.51" (14.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseSatial, Can	Capacitance	33µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency98mA @ 120HzRipple Current - High Frequency196mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.551" (14.00mm)Height - Seated (Max)-Surface Mount Land Size-Mouning TypeFackage / CaseReade y Case-Reade y Case- </td <td>Tolerance</td> <td>$\pm 20\%$</td>	Tolerance	$\pm 20\%$
Lifetime @ Temp.1000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency98mA @ 120HzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeRaida, CanPackage / CaseRaida, Can	Voltage - Rated	63V
And -55°C ~ 105°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency 98mA @ 120Hz Ripple Current - High Frequency 196mA @ 10kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radia, Can	ESR (Equivalent Series Resistance)	-
PolarizationBi-PolarApplicationsGeneral PurposeRipple Current - Low Frequency98mA @ 120HzRipple Current - High Frequency196mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency98mA @ 120HzRipple Current - High Frequency196mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency98mA @ 120HzRipple Current - High Frequency196mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Bi-Polar
Ripple Current - High Frequency196mA @ 10kHzImpedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	General Purpose
Impedance-Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	98mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	196mA @ 10kHz
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.551" (14.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Down of a second s	Package / Case	Radial, Can
Report error		Report errors?

UEP1J330MPD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UEP1J330MPD Payment Methods



UEP1J330MPD Shipping Methods



If you have any question about UEP1J330MPD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com