

UES1C100MDM1TA

UES1C100MDM1TA Information

elsener.com

Part Number UES1C100MDM1TA

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 10UF 20% 16V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UES1C100MDM1TA Specifications

Manufacturer Part NumberUES1C100MDM1TAManufacturerNichiconCategoryCapacitorsPackageRadial, CanSeriesUESCapacitance10μFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationBi-PolarApplicationsAudioRipple Current - Low Frequency-
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
PackageRadial, CanSeriesUESCapacitance $10\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $16V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. $1000 \text{Hrs} \ @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationBi-PolarApplicationsAudio
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$
Capacitance $10\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $16V$ ESR (Equivalent Series Resistance)-Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationBi-PolarApplicationsAudio
Tolerance $\pm 20\%$ Voltage - Rated $16V$ ESR (Equivalent Series Resistance) - Lifetime @ Temp. $1000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Polarization $Bi\text{-Polar}$ Applications Audio
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications Audio
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications Audio
Lifetime @ Temp. $1000 \text{Hrs} @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationBi-PolarApplicationsAudio
Operating Temperature -40°C ~ 85°C Polarization Applications Audio
Polarization Bi-Polar Applications Audio
Applications Audio
Pinnla Current Low Fraguency
Ripple Current - Low Prequency -
Ripple Current - High Frequency -
Impedance -
Lead Spacing 0.079" (2.00mm)
Size / Dimension 0.197" Dia (5.00mm)
Height - Seated (Max) 0.472" (12.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can
Report errors

UES1C100MDM1TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UES1C100MDM1TA Payment Methods



















UES1C100MDM1TA Shipping Methods













If you have any question about UES1C100MDM1TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com