



UES1H220MPM Information

ener.com

Part Number UES1H220MPM

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 22UF 20% 50V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UES1H220MPM Specifications

Manufacturer Part Number UES1H220MPM Manufacturer Nichicon Category Capacitors Package Radial, Can Series UES Capacitance 22μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications Audio Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	_	
Category Capacitors Package Radial, Can Series UES Capacitance 22µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications Audio Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	UES1H220MPM
Package Radial, Can Series UES Capacitance 22µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications Audio Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Nichicon
Package Radial, Can Series UES Capacitance 22μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications Audio Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series UES Capacitance 22µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications Audio Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 22µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications Audio Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications Audio Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	UES
Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications Audio Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Capacitance	22μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Audio Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Riover ~ 85°C -40°C ~ 85°C -40	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications Audio Ripple Current - Low Frequency -Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1000 Hrs @ 85°C -40°C ~ 85°C Bi-Polar Audio - 0.190 - 0.190 - 1.100 1.10	Voltage - Rated	50V
Operating Temperature -40°C ~ 85°C Polarization Bi-Polar Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Bi-Polar Applications Audio Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications Audio Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Bi-Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	Audio
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Ripple Current - Low Frequency	-
Lead Spacing0.197" (5.00mm)Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.551" (14.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.551" (14.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.394" Dia (10.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.551" (14.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UES1H220MPM Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UES1H220MPM Payment Methods



















UES1H220MPM Shipping Methods













If you have any question about UES1H220MPM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com