

UFG1K100MEM

UFG1K100MEM Information

www.heisener.com	Part Number Manufacturer Category Description Package	Capacitors Aluminum Electrolytic Capacitors CAP ALUM 10UF 20% 80V RADIAL Radial, Can	
1	Tuchuge	For the pricing/inventory/lead time, please contact us	∎í**2°
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UFG1K100MEM Specifications

ManufacturerNichiconCagacitorsAluminum Electrolytic CagacitorsPackageRadial, CanPackageRadial, CanSeriesUFGCapacitance10µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature90arApplicationsSinA @ 120HzRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency10mA @ 10kHzImpedance-Lied Spacing0.998° (2.50mm)Size / Dimension0.949° (12.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanPackageRadial, CanSeriesUFGCapacitance10µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsStmA @ 120HzRipple Current - Low Frequency110mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	UFG1K100MEM
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUFGCapacitance10µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationAudioRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency110mA @ 10kHzImpedance-Lad Spacing0.98° (2.50mm)Siz / Dimension0.44° (12.50mm)Sirafaer Mount Land Size-Mounting Type-Package / CaseStala, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUFGCapacitance10µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationAudioRiple Current - Low Frequency55mA @ 120HzRiple Current - High Frequency0.098° (2.50mm)Siz / Dimension0.248°Dia (6.30mm)Siz / Dimension0.402° (12.50mm)Siraface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila, Can	Category	Capacitors
SeriesUFGCapacitance10µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency55mA @ 120HzInpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can		Aluminum Electrolytic Capacitors
Capacitance10µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency55mA @ 120HzInpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseKadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency0.098" (2.50mm)Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Pockage / CaseRatial, Can	Series	UFG
Voltage - Rated80VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency55mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Capacitance	10µF
ComponentESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency55mA @ 120HzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.492" (12.50mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency110mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Voltage - Rated	80V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency110mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsAudioRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency110mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	1000 Hrs @ 85°C
ApplicationsAudioRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency110mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40° C ~ 85° C
InSint PrequencyRipple Current - Low Frequency55mA @ 120HzRipple Current - High Frequency110mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
InInRipple Current - High Frequency110mA @ 10kHzImpedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	Audio
Impedance-Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	55mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	110mA @ 10kHz
Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)0.492" (12.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	0.492" (12.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UFG1K100MEM Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UFG1K100MEM Payment Methods



UFG1K100MEM Shipping Methods



If you have any question about UFG1K100MEM, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com