

UFW1C103MHD

UFW1C103MHD Information

For Reference Only	Part Number Manufacturer Category Description Package	UFW1C103MHD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 10000UF 20% 16V RADIAL Radial, Can	
	Package	Radial, Can For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UFW1C103MHD Specifications

ManufacturerNichiconCapacitorsCapacitorsPackageRadial, CanPackageRadial, CanSeriesUFWCapacitance10000µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationAudioRipple Current - Low Frequency3.036A @ 10kHzRipple Current - High Frequency3.036A @ 10kHzImpedance-Lied Spacing0.295° (7.50mm)Size / Dimension1.398° (35.50mm)Height - Seated (Max)3.398° (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUFWCapacitance10000µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency3.036A @ 10kHzImpedance-Lead Spacing0.295°(7.50mm)Size / Dimension1.398°(35.50mm)Height - Seated (Max)1.398°(35.50mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer Part Number	UFW1C103MHD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUFWCapacitance10000µFTolerance±20%Voltage - Rated6VESR (Equivalent Series Resistance)-Deraring Temperature2000 Hrs @ 85°COperating Temperature6VarApplicationsAudioRipple Current - High Frequency2.64A @ 120HzRipple Current - High Frequency3.036A @ 10kHzImpedance-Lad Spacing0.295° (7.50mm)Size / Dimension1.398° (35.50mm)Hight - Seated (Max).398° (35.50mm)Surface Mount Land Size-Package / CaseKadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUFWCapacitance1000µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplications2.64A @ 120HzRiple Current - High Frequency3.036A @ 10kHzImpedance0.295° (7.50mm)Size / Dimension0.295° (7.50mm)Size / Dimension3.038° (35.50mm)Height - Seated (Max)1.398° (35.50mm)Surface Mount Land Size-Package / CaseKadial, Can	Category	Capacitors
SeriesUFWCapacitance10000µFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency2.64A @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension1.398" (35.50mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance10000µFTolerance±20%Voltage - Rated6VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency2.64A @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency2.64A @ 120HzBipple Current - High Frequency3.036A @ 10kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension1.398° (35.50mm)Height - Seated (Max)1.398° (35.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UFW
Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency2.64A @ 120HzBipple Current - High Frequency3.036A @ 10kHzImpedance-Lead Spacing0.295°(7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)1.398° (35.50mm)Surface Mount Land Size-Pockage / CaseRatial, Can	Capacitance	10000µF
ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency2.64A @ 120HzBipple Current - High Frequency3.036A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency2.64A @ 120HzRipple Current - High Frequency3.036A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can	Voltage - Rated	16V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency2.64A @ 120HzRipple Current - High Frequency3.036A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsAudioRipple Current - Low Frequency2.64A @ 120HzRipple Current - High Frequency3.036A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsAudioRipple Current - Low Frequency2.64A @ 120HzRipple Current - High Frequency3.036A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
InInRipple Current - Low Frequency2.64A @ 120HzRipple Current - High Frequency3.036A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of a constrain	Applications	Audio
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	2.64A @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	3.036A @ 10kHz
Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.398" (35.50mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.709" Dia (18.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.398" (35.50mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UFW1C103MHD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UFW1C103MHD Payment Methods



UFW1C103MHD Shipping Methods



If you have any question about UFW1C103MHD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com