



UFW1J102MHD Information



For Reference Only

Part Number UFW1J102MHD

Manufacturer Nichicon
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1000UF 20% 63V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UFW1J102MHD Specifications

Manufacturer Part Number UFW1J102MHD Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series UFW Capacitance 1000µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 1.3A @ 120Hz Ripple Current - High Frequency 1.495A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm)		
CategoryCapacitorsPackageRadial, CanSeriesUFWCapacitance1000μFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency1.3A @ 120HzRipple Current - High Frequency1.495A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)	Manufacturer Part Number	UFW1J102MHD
Aluminum Electrolytic Capacitors Package Radial, Can UFW Capacitance 1000µF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance)	Manufacturer	Nichicon
PackageRadial, CanSeriesUFWCapacitance1000μFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency1.3A @ 120HzRipple Current - High Frequency1.495A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)	Category	Capacitors
SeriesUFWCapacitance1000µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency1.3A @ 120HzRipple Current - High Frequency1.495A @ 10kHzImpedance-Lead Spacing0.295" (7.50mm)		Aluminum Electrolytic Capacitors
Capacitance 1000μF Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 1.3A @ 120Hz Ripple Current - High Frequency 1.495A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm)	Package	Radial, Can
Tolerance ±20% Voltage - Rated 63V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 1.3A @ 120Hz Ripple Current - High Frequency 1.495A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm)	Series	UFW
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency 1.495A @ 10kHz Impedance - Lead Spacing 63V 63V 63V 63V 63V 63V 63V 63	Capacitance	1000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency 1.3A @ 120Hz Ripple Current - High Frequency 1.495A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm)	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 1.3A @ 120Hz Ripple Current - High Frequency 1.495A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm)	Voltage - Rated	63V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications Audio Ripple Current - Low Frequency 1.3A @ 120Hz Ripple Current - High Frequency 1.495A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm)	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications Audio Ripple Current - Low Frequency 1.3A @ 120Hz Ripple Current - High Frequency 1.495A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm)	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 1.3A @ 120Hz 1.495A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm)	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 1.3A @ 120Hz 1.495A @ 10kHz Impedance - Lead Spacing 0.295" (7.50mm)	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 1.495A @ 10kHz - 0.295" (7.50mm)	Applications	Audio
Impedance-Lead Spacing0.295" (7.50mm)	Ripple Current - Low Frequency	1.3A @ 120Hz
Lead Spacing 0.295" (7.50mm)	Ripple Current - High Frequency	1.495A @ 10kHz
	Impedance	-
Size / Dimension 0.630" Dia (16.00mm)	Lead Spacing	0.295" (7.50mm)
	Size / Dimension	0.630" Dia (16.00mm)
Height - Seated (Max) 0.984" (25.00mm)	Height - Seated (Max)	0.984" (25.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

UFW1J102MHD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UFW1J102MHD Payment Methods



















UFW1J102MHD Shipping Methods













If you have any question about UFW1J102MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com