

UFW1V153MRD

UFW1V153MRD Information

www.ean lettree.com	Part Number Manufacturer Category Description Package	UFW1V153MRD Nichicon Capacitors Aluminum Electrolytic Capacitors CAP ALUM 15000UF 20% 35V RADIAL Radial, Can For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



UFW1V153MRD Specifications

CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUFWCapacitance15000µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationAudioApplicationsAudioRipple Current - Low Frequency4.945A @ 100HzNipple Current - High Frequency0.9492" (12.50mm)Size / Dimension1.969" (50.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Pokage / CaseMain CanPokage / CaseAdia, Can	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUFWCapacitance15000µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationAudioApplicationsAudioRipple Current - High Frequency4.945A @ 100 HrzImpedance-Lead Spacing0.942" (12.50mm)Size / Dimension1.969" (50.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Pounting TypeAida, Can	Manufacturer Part Number	UFW1V153MRD
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesUFWCapacitance15000µFTolerance±20%Voltage - RatedSvESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationAudioRipple Current - Low Frequency4.3A @ 120HzRipple Current - High Frequency0.4945A @ 10kHzImpedance-Lead Spacing0.984" Dia (25.00mm)Size / Dimension1.969" (50.00mm)Strace Mount Land Size-Mounting TypeFancage (CasePackage / CaseStrace Mount Land SizePackage / CaseRadial, Can	Manufacturer	Nichicon
PackageRadial, CanSeriesUFWCapacitance1500µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Operating Temperature2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - High Frequency4.34 @ 120HzImpedance0.492*(12.50mm)Siz / Dimension0.492*(12.50mm)Siz / Dimension1.969*(50.00mm)Strace Mount Land Size-Mounting TypeHolePackage / CaseKalial, Can	Category	Capacitors
SeriesUFWCapacitance15000μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency4.945A @ 10kHzImpedance-Lead Spacing0.984* Dia (25.00mm)Siz / Dimension1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can		Aluminum Electrolytic Capacitors
Capacitance1500µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency4.3A @ 120HzImpedance-Lead Spacing0492° (12.50mm)Size / Dimension0.984° Dia (25.00mm)Height - Seated (Max)1.969° (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency4.3A @ 120HzImpedance-Lead Spacing0.984" Dia (25.00mm)Size / Dimension1.969" (50.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	UFW
Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency4.3A @ 120HzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension1.969" (50.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can	Capacitance	15000µF
For the series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency4.3A @ 120HzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency4.3A @ 120HzRipple Current - High Frequency4.945A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	Voltage - Rated	35V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency4.3A @ 120HzRipple Current - High Frequency4.945A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, CanRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsAudioRipple Current - Low Frequency4.3A @ 120HzRipple Current - High Frequency4.945A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsAudioApplicationsAudioRipple Current - Low Frequency4.3A @ 120HzRipple Current - High Frequency4.945A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
IIAligneRipple Current - Low Frequency4.3A @ 120HzRipple Current - High Frequency4.945A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
ArArRipple Current - High Frequency4.945A @ 10kHzImpedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Applications	Audio
Impedance-Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	4.3A @ 120Hz
Lead Spacing0.492" (12.50mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	4.945A @ 10kHz
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.492" (12.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.969" (50.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

UFW1V153MRD Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

UFW1V153MRD Payment Methods



UFW1V153MRD Shipping Methods



If you have any question about UFW1V153MRD, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com