



UHA1H2R2MHD Information

Heisener.com

Part Number UHA1H2R2MHD

Manufacturer Nichicon Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 2.2UF 20% 50V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UHA1H2R2MHD Specifications

Manufacturer Part Number Manufacturer Nichicon Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can UHA Capacitance UHA Capacitance 2.2µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mausting Temperature 1 Through Hele 1	•	
Category Capacitors Package Radial, Can Series UHA Capacitance 2.2μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -25°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 5A @ 15.75kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.024" (26.00mm) Surface Mount Land Size -	Manufacturer Part Number	UHA1H2R2MHD
Package Radial, Can Series UHA Capacitance 2.2μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -25°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 5A @ 15.75kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.024" (26.00mm) Surface Mount Land Size -	Manufacturer	Nichicon
Package Radial, Can Series UHA Capacitance 2.2µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -25°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 5A @ 15.75kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.024" (26.00mm) Surface Mount Land Size -	Category	Capacitors
Series UHA Capacitance 2.2μF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -25°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 5A @ 15.75kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.024" (26.00mm) Surface Mount Land Size -		Aluminum Electrolytic Capacitors
Capacitance 2.2µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -25°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 5A @ 15.75kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.024" (26.00mm) Surface Mount Land Size -	Package	Radial, Can
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -25°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 5A @ 15.75kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.024" (26.00mm) Surface Mount Land Size -	Series	UHA
Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -25°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 5A @ 15.75kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.024" (26.00mm) Surface Mount Land Size -	Capacitance	2.2µF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 5A @ 15.75kHz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size -	Tolerance	±20%
Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -25°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 5A @ 15.75kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.024" (26.00mm) Surface Mount Land Size -	Voltage - Rated	50V
Operating Temperature -25°C ~ 85°C Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 5A @ 15.75kHz Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size -25°C ~ 85°C Bi-Polar General Purpose - 0.492" Dia (12.50mm) 1.024" (26.00mm)	ESR (Equivalent Series Resistance)	-
Polarization Bi-Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 5A @ 15.75kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.024" (26.00mm) Surface Mount Land Size -	Lifetime @ Temp.	1000 Hrs @ 105°C
Applications Ripple Current - Low Frequency	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency - SA @ 15.75kHz Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.024" (26.00mm) Surface Mount Land Size	Polarization	Bi-Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.024" (26.00mm) Surface Mount Land Size -	Applications	General Purpose
Impedance - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.024" (26.00mm) Surface Mount Land Size -	Ripple Current - Low Frequency	-
Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 1.024" (26.00mm) Surface Mount Land Size -	Ripple Current - High Frequency	5A @ 15.75kHz
Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)1.024" (26.00mm)Surface Mount Land Size-	Impedance	-
Height - Seated (Max) Surface Mount Land Size 1.024" (26.00mm) -	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size -	Size / Dimension	0.492" Dia (12.50mm)
	Height - Seated (Max)	1.024" (26.00mm)
Mounting Type Through Hole	Surface Mount Land Size	-
Mounting Type	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

UHA1H2R2MHD Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UHA1H2R2MHD Payment Methods



















UHA1H2R2MHD Shipping Methods













If you have any question about UHA1H2R2MHD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com