

UHD160-1004 Information

Heisener.com

Part Number UHD160-1004 Manufacturer ERP Power, LLC

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 3.3V 160W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UHD160-1004 Specifications

Manufacturer Part Number UHD160-1004 Manufacturer ERP Power, LLC Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	-	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Manufacturer Part Number	UHD160-1004
Package - Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Manufacturer	ERP Power, LLC
Package - Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Category	Power Supplies - External/Internal (Off-Board)
Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Package	-
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 3.3V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 20A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Series	UHD160
Voltage - Input90 ~ 264 VACVoltage - Output 13.3VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)20APower (Watts)160WApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency90%Operating Temperature-20°C ~ 70°CFeaturesUniversal InputMounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Type	Open Frame
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Features Universal Input Mounting Type Chassis Mount Size / Dimension 3.3V 3.3V 3.3V 3.3V 3.3V 4.00V 4.000V 4.00° L x 2.00° W x 1.08° H (101.6mm x 50.8mm x 27.4mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension - Output 2 - Output 3 - Courrent - Output (Max) - Commercial), Medical 4kV (4000V) - Commercial), Medical -	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension - Output (Max) - Outp	Voltage - Output 1	3.3V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension - Output 4 - Output 4 - Output 20A - Output 3 - Output 4 - Output 20A - Output 3 - Output 4 - O	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 20A 160W 100	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 160W 4kV (4000V) 4kV (4000V) 50% Chassis Mount 4kV (4000V)	Voltage - Output 4	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Current - Output (Max)	20A
Voltage - Isolation $4kV (4000V)$ Efficiency 90% Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features Universal Input Mounting Type Chassis Mount Size / Dimension $4.00^{\circ}\text{L x } 2.00^{\circ}\text{W x } 1.08^{\circ}\text{H } (101.6\text{mm x } 50.8\text{mm x } 27.4\text{mm})$	Power (Watts)	160W
Efficiency 90% Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features Universal Input Mounting Type Chassis Mount Size / Dimension $4.00^{\circ}\text{L x } 2.00^{\circ}\text{W x } 1.08^{\circ}\text{H } (101.6\text{mm x } 50.8\text{mm x } 27.4\text{mm})$	Applications	ITE (Commercial), Medical
Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00° L x 2.00° W x 1.08° H (101.6 mm x 50.8 mm x 27.4 mm)	Voltage - Isolation	4kV (4000V)
Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Efficiency	90%
Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Operating Temperature	-20°C ~ 70°C
Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Features	Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)
The post of the same and the sa		Report errors?

UHD160-1004 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UHD160-1004 Payment Methods



















UHD160-1004 Shipping Methods













If you have any question about UHD160-1004, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com