

UHD160-1007 Information

Heisener.com

Part Number UHD160-1007 Manufacturer ERP Power, LLC

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 29V 160W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UHD160-1007 Specifications

Manufacturer Part Number UHD160-1007 Manufacturer ERP Power, LLC Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 29V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.5A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm) Report errors?			
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 29V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.5A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Manufacturer Part Number	UHD160-1007	
AC DC Converters Package - Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 29V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.5A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Manufacturer	ERP Power, LLC	
Package - Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 29V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.5A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 29V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.5A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)		AC DC Converters	
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 29V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.5A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Package	-	
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 29V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.5A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Series	UHD160	
Voltage - Input 90 ~ 264 VAC Voltage - Output 1 29V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.5A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Type	Open Frame	
Voltage - Output 1 29V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5.5A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Number of Outputs	1	
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) Current - Output (Max) Current - Output (Max) Current - Output (Max) Commercial), Medical Commercia	Voltage - Input	90 ~ 264 VAC	
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) S.5A Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension - Output (Max) - Chassis Mount - Chassis Mount 4kV (4000V) Chassis Mount 4kV (4000V) Chassis Mount Chassis Mount 400" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Voltage - Output 1	29V	
Voltage - Output 4 Current - Output (Max) 5.5A Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension -20°L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Voltage - Output 2	-	
Current - Output (Max) 5.5A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 5.5A 5.5A 160W Nedical 4kV (4000V) Commercial), Medical 4kV (4000V) 60% 4kV (4000V) 60% 60% 60% 60% 60% 60% 60% 60	Voltage - Output 3	-	
Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 160W AkV (4000V) Commercial), Medical 4kV (4000V) 90% 90% Chassis Mount 101.6mm x 50.8mm x 27.4mm)	Voltage - Output 4	-	
Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Current - Output (Max)	5.5A	
Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Power (Watts)	160W	
Efficiency 90% 90% 90% 90% 90% 90% 90% 90% 90% 90%	Applications	ITE (Commercial), Medical	
Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Voltage - Isolation	4kV (4000V)	
Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Efficiency	90%	
Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Operating Temperature	-20°C ~ 70°C	
Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Features	Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	
		Re	port errors?

UHD160-1007 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UHD160-1007 Payment Methods



















UHD160-1007 Shipping Methods













If you have any question about UHD160-1007, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com