



UHD160-1009 Information

Heisener.com

Part Number UHD160-1009 **Manufacturer** ERP Power, LLC

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 36V 160W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









UHD160-1009	Specifications
-------------	-----------------------

Manufacturer Part Number UHD160-1009 Manufacturer ERP Power, LLC Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm) Report errors?	-	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Manufacturer Part Number	UHD160-1009
Package - Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Manufacturer	ERP Power, LLC
Package - Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Category	Power Supplies - External/Internal (Off-Board)
Series UHD160 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Package	-
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Series	UHD160
Voltage - Input 90 ~ 264 VAC Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Туре	Open Frame
Voltage - Output 1 36V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.4A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Features Universal Input Mounting Type Chassis Mount Size / Dimension - Output (Max) - Current - Output (Ma	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension - Output (Max) - A4A - A4A Power (Watts) A4V A4A Power (Watts) A4V A4A Power (Watts) A4V A4A A4A A4A A4A A4A A4A A4	Voltage - Output 1	36V
Voltage - Output 4 Current - Output (Max) 4.4A Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension -4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Voltage - Output 2	-
Current - Output (Max) 4.4A Power (Watts) 160W Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.40" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 160W AkV (4000V) Universal Input Chassis Mount 4kV (4000V) 4kV (4000V) 100	Voltage - Output 4	-
Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 90% Operating Temperature -20°C ~ 70°C Features Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Current - Output (Max)	4.4A
Voltage - Isolation $4kV (4000V)$ Efficiency 90% Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features Universal Input Mounting Type Chassis Mount Size / Dimension $4.00''$ L x $2.00''$ W x $1.08''$ H $(101.6\text{mm} \times 50.8\text{mm} \times 27.4\text{mm})$	Power (Watts)	160W
Efficiency 90% 90% Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Universal Input Mounting Type Chassis Mount Size / Dimension 4.00° L x 2.00° W x 1.08° H (101.6 mm x 50.8 mm x 27.4 mm)	Applications	ITE (Commercial), Medical
Operating Temperature -20°C ~ 70°C Universal Input Mounting Type Chassis Mount Size / Dimension Chassis Mount 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Voltage - Isolation	4kV (4000V)
Features Universal Input Mounting Type Chassis Mount Size / Dimension Universal Input Chassis Mount 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Efficiency	90%
Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Operating Temperature	-20°C ~ 70°C
Size / Dimension 4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)	Features	Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	4.00" L x 2.00" W x 1.08" H (101.6mm x 50.8mm x 27.4mm)
		Report errors?

UHD160-1009 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

UHD160-1009 Payment Methods



















UHD160-1009 Shipping Methods













If you have any question about UHD160-1009, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com