



### **UHD1E331MPD Information**



For Reference Only

Part Number UHD1E331MPD

Manufacturer Nichicon Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 330UF 20% 25V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **UHD1E331MPD Specifications**

Manufacturer Part Number         UHD1E331MPD           Manufacturer         Nichicon           Category         Capacitors           Package         Radial, Can           Series         UHD           Capacitance         330µF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         696.5mA @ 120Hz           Ripple Current - High Frequency         995mA @ 100kHz           Impedance         56 mOhms           Lead Spacing         0.138" (3.50mm)           Size / Dimension         0.315" Dia (8.00mm)           Height - Seated (Max)         0.650" (16.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole		
Category         Capacitors           Package         Radial, Can           Series         UHID           Capacitance         330µF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         696.5mA @ 120Hz           Ripple Current - High Frequency         995mA @ 100kHz           Impedance         56 mOhms           Lead Spacing         0.138" (3.50mm)           Size / Dimension         0.315" Dia (8.00mm)           Height - Seated (Max)         0.650" (16.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	Manufacturer Part Number	UHD1E331MPD
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesUHDCapacitance330µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency696.5mA @ 120HzRipple Current - High Frequency995mA @ 100kHzImpedance56 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	Nichicon
Package         Radial, Can           Series         UHD           Capacitance         330μF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         696.5mA @ 120Hz           Ripple Current - High Frequency         995mA @ 100kHz           Impedance         56 mOhms           Lead Spacing         0.138" (3.50mm)           Size / Dimension         0.315" Dia (8.00mm)           Height - Seated (Max)         0.650" (16.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	Category	Capacitors
Series         UHD           Capacitance         330µF           Tolerance         ±20%           Voltage - Rated         25V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         3000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         696.5mA @ 120Hz           Ripple Current - High Frequency         995mA @ 100kHz           Impedance         56 mOhms           Lead Spacing         0.138" (3.50mm)           Size / Dimension         0.315" Dia (8.00mm)           Height - Seated (Max)         0.650" (16.50mm)           Surface Mount Land Size         -           Mounting Type         Through Hole		Aluminum Electrolytic Capacitors
Capacitance330μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency696.5mA @ 120HzRipple Current - High Frequency995mA @ 100kHzImpedance56 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can
Tolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency696.5mA @ 120HzRipple Current - High Frequency995mA @ 100kHzImpedance56 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	UHD
Voltage - Rated25VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency696.5mA @ 120HzRipple Current - High Frequency995mA @ 100kHzImpedance56 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	330μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  3000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  696.5mA @ 120Hz  Ripple Current - High Frequency  995mA @ 100kHz  Impedance  56 mOhms  Lead Spacing  0.138" (3.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  - Through Hole	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 105°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  696.5mA @ 120Hz  Ripple Current - High Frequency  995mA @ 100kHz  Impedance  56 mOhms  Lead Spacing  0.138" (3.50mm)  Size / Dimension  Height - Seated (Max)  O.650" (16.50mm)  Surface Mount Land Size  -  Mounting Type  Through Hole	Voltage - Rated	25V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 696.5mA @ 120Hz Ripple Current - High Frequency 995mA @ 100kHz Impedance 56 mOhms Lead Spacing 0.138" (3.50mm) Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.650" (16.50mm) Surface Mount Land Size - Mounting Type Through Hole	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 696.5mA @ 120Hz  Ripple Current - High Frequency 995mA @ 100kHz  Impedance 56 mOhms  Lead Spacing 0.138" (3.50mm)  Size / Dimension 0.315" Dia (8.00mm)  Height - Seated (Max) 0.650" (16.50mm)  Surface Mount Land Size - Through Hole	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Personal Spacing  Current - High Frequency  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  General Purpose  696.5mA @ 120Hz  995mA @ 100kHz  100kHz  101kHz  101kHz	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  995mA @ 100kHz  Impedance  56 mOhms  Lead Spacing  0.138" (3.50mm)  Size / Dimension  0.315" Dia (8.00mm)  Height - Seated (Max)  0.650" (16.50mm)  Surface Mount Land Size  Mounting Type  Through Hole	Polarization	Polar
Ripple Current - High Frequency  Impedance  56 mOhms  Lead Spacing  0.138" (3.50mm)  Size / Dimension  0.315" Dia (8.00mm)  Height - Seated (Max)  0.650" (16.50mm)  Surface Mount Land Size  Mounting Type  Through Hole	Applications	General Purpose
Impedance56 mOhmsLead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	696.5mA @ 120Hz
Lead Spacing0.138" (3.50mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	995mA @ 100kHz
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.650" (16.50mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	56 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  0.650" (16.50mm)  - Through Hole	Lead Spacing	0.138" (3.50mm)
Surface Mount Land Size - Through Hole	Size / Dimension	0.315" Dia (8.00mm)
Mounting Type Through Hole	Height - Seated (Max)	0.650" (16.50mm)
	Surface Mount Land Size	-
	Mounting Type	Through Hole
Package / Case Radial, Can	Package / Case	Radial, Can
Report errors?		Report errors?

#### **UHD1E331MPD Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **UHD1E331MPD Payment Methods**



















## **UHD1E331MPD Shipping Methods**













If you have any question about UHD1E331MPD, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com